

Package ‘leaflet.providers’

November 10, 2019

Type Package

Title Leaflet Providers

Version 1.9.0

Description Contains third-party map tile provider information from 'Leaflet.js', <<https://github.com/leaflet-extras/leaflet-providers>>, to be used with the 'leaflet' R package. Additionally, 'leaflet.providers' enables users to retrieve up-to-date provider information between package updates.

License BSD_2_clause + file LICENSE

Encoding UTF-8

LazyData true

Depends R (>= 2.10)

Suggests V8, jsonlite, testthat (>= 2.1.0)

Language en-US

RoxygenNote 6.1.1

URL <https://github.com/rstudio/leaflet.providers>

BugReports <https://github.com/rstudio/leaflet.providers/issues>

Collate 'providers_data.R' 'get_current_providers.R'

NeedsCompilation no

Author Leslie Huang [aut],
Barret Schloerke [ctb, cre] (<<https://orcid.org/0000-0001-9986-114X>>),
Leaflet Providers contributors [ctb, cph] (Leaflet Providers plugin),
RStudio [cph, fnd]

Maintainer Barret Schloerke <barret@rstudio.com>

Repository CRAN

Date/Publication 2019-11-09 23:40:09 UTC

R topics documented:

| | |
|-----------------------------|---|
| get_providers | 2 |
| providers_default | 3 |
| providers_loaded | 3 |
| use_providers | 4 |

| | |
|--------------|----------|
| Index | 5 |
|--------------|----------|

| | |
|---------------|---|
| get_providers | <i>Fetch leaflet providers from Leaflet.js.</i> |
|---------------|---|

Description

Fetch leaflet providers from Leaflet.js.

Usage

```
get_providers(version_num = NULL)
```

Arguments

| | |
|-------------|--|
| version_num | Version number with which to update leaflet providers. If NULL, fetches most recent version. |
|-------------|--|

Value

leaflet_providers object containing providers_version_num, providers_data, providers_details_data, src

Examples

```
if (require("V8") && require("jsonlite")) {
  get_providers()
  get_providers("1.8.0")
}
```

| | |
|-------------------|---|
| providers_default | <i>Return default providers, providers_details, version, and HTML Dependency.</i> |
|-------------------|---|

Description

Return default providers, providers_details, version, and HTML Dependency.

Usage

```
providers_default()
```

Value

leaflet_providers object containing providers_version_num, providers, providers_details, and src

Examples

```
str(providers_default(), max = 3, list.len = 4)
```

| | |
|------------------|--|
| providers_loaded | <i>Return currently loaded providers, providers_details, version, and HTML Dependency.</i> |
|------------------|--|

Description

Return currently loaded providers, providers_details, version, and HTML Dependency.

Usage

```
providers_loaded()
```

Value

leaflet_providers object containing providers_version_num, providers, providers_details, and src

Examples

```
str(providers_loaded(), max = 3, list.len = 4)
```

| | |
|---------------|---|
| use_providers | <i>Use a custom leaflet_providers object, e.g. providers data fetched with get_providers, with the leaflet package.</i> |
|---------------|---|

Description

Use a custom leaflet_providers object, e.g. providers data fetched with [get_providers](#), with the leaflet package.

Usage

```
use_providers(providers_info = NULL)
```

Arguments

providers_info A custom leaflet_providers object. If NULL, uses default providers.

Examples

```
if (require("V8") && require("jsonlite")) {  
  # Set providers to latest providers  
  use_providers(get_providers())  
  
  # Set providers to a custom providers object (specific version number)  
  use_providers(get_providers("1.4.0"))  
  use_providers("1.4.0")  
}
```

Index

`get_providers`, 2, 4

`providers_default`, 3

`providers_loaded`, 3

`use_providers`, 4