

# Package ‘politeness’

February 26, 2022

**Type** Package

**Title** Detecting Politeness Features in Text

**Version** 0.8.6

**Author** Mike Yeomans, Alejandro Kantor, Dustin Tingley

**Maintainer** Mike Yeomans <mk.yeomans@gmail.com>

**Description** Detecting markers of politeness in English natural language. This package allows researchers to easily visualize and quantify politeness between groups of documents. This package combines prior research on the linguistic markers of politeness. We thank the Spencer Foundation, the Hewlett Foundation, and Harvard's Institute for Quantitative Social Science for support.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Depends** R (>= 3.5.0)

**Imports** tm, quanteda, ggplot2, parallel, spacyr, textir, glmnet,  
data.table, stringr, stringi

**RoxygenNote** 7.1.2

**Suggests** knitr, rmarkdown, testthat

**VignetteBuilder** knitr

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2022-02-26 13:40:02 UTC

## R topics documented:

bowl_offers . . . . .	2
feature_table . . . . .	3
findPoliteTexts . . . . .	3
hedge_list . . . . .	4
negative_list . . . . .	5
phone_offers . . . . .	5

politeness	6
politenessPlot	7
politenessProjection	9
polite_dicts	10
positive_list	11
receptiveness	11
receptive_polite	12
receptive_train	12
uk2us	13

---

<b>bowl_offers</b>	<i>Purchase offers for bowl</i>
--------------------	---------------------------------

---

## Description

A dataset containing the purchase offer message and a label indicating if the writer was assigned to be warm (1) or tough (0)

## Usage

`bowl_offers`

## Format

A data frame with 70 rows and 2 variables:

**message** character of purchase offer message

**condition** binary label indicating if message is warm or tough

## Source

Jeong, M., Minson, J., Yeomans, M. & Gino, F. (2019).

"Communicating Warmth in Distributed Negotiations is Surprisingly Ineffective." Study 3.

Study 3. <https://osf.io/t7sd6/>

---

feature_table	<i>Table of Politeness Features</i>
---------------	-------------------------------------

---

### Description

This table describes all the text features extracted in this package. See vignette for details.

### Usage

```
feature_table
```

### Format

A data.frame with information about the politeness features.

---

findPoliteTexts	<i>Find polite text</i>
-----------------	-------------------------

---

### Description

Finds examples of most or least polite text in a corpus

### Usage

```
findPoliteTexts(  
  text,  
  df_polite,  
  covar,  
  type = c("most", "least", "both"),  
  num_docs = 5L,  
  ...  
)
```

### Arguments

text	a character vector of texts.
df_polite	a data.frame with politeness features, as outputed by <code>politeness</code> , used to train model.
covar	a vector of politeness labels, or other covariate.
type	a string indicating if function should return the most or least polite texts or both. If <code>length &gt; 1</code> only first value is used.
num_docs	integer of number of documents to be returned. Default is 5.
...	additional parameters to be passed to <code>politenessProjection</code> .

**Details**

Function returns a data.frame ranked by (more or least) politeness. If type == 'most', the num\_docs most polite texts will be returned. If type == 'least', the num\_docs least polite texts will be returned. If type == 'both', both most and least polite text will be returned. If num\_docs is even, half will be most and half least polite else half + 1 will be most polite.

df\_polite must have the same number of rows as the length(text) and length(covar).

**Value**

data.frame with texts ranked by (more or least) politeness. See details for more information.

**Examples**

```
data("phone_offers")
polite.data<-politeness(phone_offers$message, parser="none", drop_blank=FALSE)

findPoliteTexts(phone_offers$message,
                polite.data,
                phone_offers$condition,
                type = "most",
                num_docs = 5)

findPoliteTexts(phone_offers$message,
                polite.data,
                phone_offers$condition,
                type = "least",
                num_docs = 10)
```

**Description**

Hedges

**Usage**

`hedge_list`

**Format**

A list of 72 hedging words.

---

negative_list	<i>Negative Emotions List</i>
---------------	-------------------------------

---

**Description**

Negative words.

**Usage**

```
negative_list
```

**Format**

A list of 4783 negatively-valenced words

---

phone_offers	<i>Purchase offers for phone</i>
--------------	----------------------------------

---

**Description**

A dataset containing the purchase offer message and a label indicating if the writer was assigned to be warm (1) or tough (0)

**Usage**

```
phone_offers
```

**Format**

A data frame with 355 rows and 2 variables:

**message** character of purchase offer message

**condition** binary label indicating if message is warm or tough

**Source**

Jeong, M., Minson, J., Yeomans, M. & Gino, F. (2019).

"Communicating Warmth in Distributed Negotiations is Surprisingly Ineffective."

Study 1. <https://osf.io/t7sd6/>

---

## Description

Detects linguistic markers of politeness in natural language. This function is the workhorse of the politeness package, taking an N-length vector of text documents and returning an N-row data.frame of feature counts.

## Usage

```
politeness(
  text,
  parser = c("none", "spacy"),
  metric = c("count", "binary", "average"),
  drop_blank = FALSE,
  uk_english = FALSE,
  num_mc_cores = 1
)
```

## Arguments

text	character A vector of texts, each of which will be tallied for politeness features.
parser	character Name of dependency parser to use (see details). Without a dependency parser, some features will be approximated, while others cannot be calculated at all.
metric	character What metric to return? Raw feature count totals, Binary presence/absence of features, or feature counts per word Default is "count".
drop_blank	logical Should features that were not found in any text be removed from the data.frame? Default is FALSE
uk_english	logical Does the text contain any British English spelling? Including variants (e.g. Canadian). Default is FALSE
num_mc_cores	integer Number of cores for parallelization. Default is 1, but we encourage users to try <code>parallel::detectCores()</code> if possible.

## Details

Some politeness features depend on part-of-speech tagged sentences (e.g. "bare commands" are a particular verb class). To include these features in the analysis, a POS tagger must be initialized beforehand - we currently support SpaCy which must be installed separately in Python (see example for implementation).

## Value

a data.frame of politeness features, with one row for every item in 'text'. Possible politeness features are listed in [feature\\_table](#)

## References

Brown, P., & Levinson, S. C. (1987). Politeness: Some universals in language usage (Vol. 4). Cambridge university press.

Danescu-Niculescu-Mizil, C., Sudhof, M., Jurafsky, D., Leskovec, J., & Potts, C. (2013). A computational approach to politeness with application to social factors. arXiv preprint arXiv:1306.6078.

Voigt, R., Camp, N. P., Prabhakaran, V., Hamilton, W. L., ... & Eberhardt, J. L. (2017). Language from police body camera footage shows racial disparities in officer respect. Proceedings of the National Academy of Sciences, 201702413.

## Examples

```
data("phone_offers")

politeness(phone_offers$message, parser="none", drop_blank=FALSE)

colMeans(politeness(phone_offers$message, parser="none", metric="binary", drop_blank=FALSE))
colMeans(politeness(phone_offers$message, parser="none", metric="count", drop_blank=FALSE))

dim(politeness(phone_offers$message, parser="none", drop_blank=FALSE))
dim(politeness(phone_offers$message, parser="none", drop_blank=TRUE))

## Not run:
# Detect multiple cores automatically for parallel processing
politeness(phone_offers$message, num_mc_cores=parallel::detectCores())

# Connect to SpaCy installation for part-of-speech features
install.packages("spacyr")
spacyr::spacy_initialize(python_executable = PYTHON_PATH)
politeness(phone_offers$message, parser="spacy", drop_blank=FALSE)

## End(Not run)
```

---

politenessPlot                    *Politeness plot*

---

## Description

Plots the prevalence of politeness features in documents, divided by a binary covariate.

## Usage

```
politenessPlot(
  df_polite,
  split = NULL,
```

```

  split_levels = NULL,
  split_name = NULL,
  split_cols = c("firebrick", "navy"),
  top_title = "",
  drop_blank = 0.05,
  middle_out = 0.5,
  CI = 0.68
)

```

## Arguments

df_polite	a data.frame with politeness features calculated from a document set, as output by <b>politeness</b> .
split	a vector of covariate values. must have a length equal to the number of documents included in df_polite. No NA values allowed.
split_levels	character vector of length 2 default NULL. Labels for covariate levels for legend. If NULL, this will be inferred from split.
split_name	character default NULL. Name of the covariate for legend.
split_cols	character vector of length 2. Name of colors to use.
top_title	character default "". Title of plot.
drop_blank	Features less prevalent than this in the sample value are excluded from the plot. To include all features, set to 0
middle_out	Features less distinctive than this value (measured by p-value of t-test) are excluded. Defaults to 1 (i.e. include all).
CI	Coverage of error bars. Defaults to 0.68 (i.e. standard error).

## Details

Length of `split` must be the same as number of rows of `df_polite`. Typically `split` should be a two-category variable. However, if a continuous covariate is given, then the top and bottom terciles of that distribution are treated as the two categories (while dropping data from the middle tercile).

## Value

a ggplot of the prevalence of politeness features, conditional on `split`. Features are sorted by variance-weighted log odds ratio.

## Examples

```

data("phone_offers")

polite.data<-politeness(phone_offers$message, parser="none", drop_blank=FALSE)

politeness::politenessPlot(polite.data,
                           split=phone_offers$condition,
                           split_levels = c("Tough", "Warm"),
                           split_name = "Condition",

```

```

top_title = "Average Feature Counts")

polite.data<-politeness(phone_offers$message, parser="none", metric="binary", drop_blank=FALSE)

politeness::politenessPlot(polite.data,
                           split=phone_offers$condition,
                           split_levels = c("Tough", "Warm"),
                           split_name = "Condition",
                           top_title = "Binary Feature Use")

```

---

politenessProjection *Politeness projection*

---

## Description

Training and projecting a regression model of politeness.

## Usage

```

politenessProjection(
  df_polite_train,
  covar = NULL,
  df_polite_test = NULL,
  classifier = c("glmnet", "mnir"),
  cv_folds = NULL,
  ...
)

```

## Arguments

df_polite_train	a data.frame with politeness features as outputed by <code>politeness</code> used to train model.
covar	a vector of politeness labels, or other covariate.
df_polite_test	optional data.frame with politeness features as outputed by <code>politeness</code> used for out-of-sample fitting. Must have same feature set as polite_train (most easily achieved by setting dropblank=FALSE in both calls to <code>politeness</code> ).
classifier	name of classification algorithm. Defaults to "glmnet" (see <code>glmnet</code> ) but "mnir" (see <code>mnir</code> ) is also available.
cv_folds	Number of outer folds for projection of training data. Default is NULL (i.e. no nested cross-validation). However, positive values are highly recommended (e.g. 10) for in-sample accuracy estimation.
...	additional parameters to be passed to the classification algorithm.

**Details**

List:

- `train_proj` projection of politeness model within training set.
- `test_proj` projection of politeness model onto test set (i.e. out-of-sample).
- `train_coef` coefficients from the trained model.

**Value**

List of `df_polite_train` and `df_polite_test` with projection. See details.

**Examples**

```
data("phone_offers")
data("bowl_offers")

polite.data<-politeness(phone_offers$message, parser="none", drop_blank=FALSE)

polite.holdout<-politeness(bowl_offers$message, parser="none", drop_blank=FALSE)

project<-politenessProjection(polite.data,
                                phone_offers$condition,
                                polite.holdout)

# Difference in average politeness across conditions in the new sample.

mean(project$test_proj[bowl_offers$condition==1])
mean(project$test_proj[bowl_offers$condition==0])
```

---

`polite_dicts`

*Feature Dictionaries*

---

**Description**

Six dictionary-like features for the detector: Negations; Pauses; Swearing; Pronouns; Formal Titles; and Informal Titles.

**Usage**

`polite_dicts`

**Format**

A list of six `quanteda::dictionary` objects

---

positive_list	<i>Positive Emotions List</i>
---------------	-------------------------------

---

**Description**

Positive words.

**Usage**

```
positive_list
```

**Format**

A list of 2006 positively-valenced words

---

receptiveness	<i>Conversational Receptiveness</i>
---------------	-------------------------------------

---

**Description**

Pre-trained model to detect conversational receptiveness

**Usage**

```
receptiveness(texts, num_mc_cores = 1)
```

**Arguments**

texts character A vector of texts, each of which will be tallied for politeness features.  
num\_mc\_cores integer Number of cores for parallelization.

**Details**

This is a wrapper around a pre-trained model of "conversational receptiveness". The model trained from Study 1 of that paper can be applied to new text with a single function. This model requires grammar parsing via SpaCy. Please see [spacyr](#) for details on installation.

**Value**

a vector with receptiveness scores

**References**

Yeomans, M., Minson, J., Collins, H., Chen, F. & Gino, F. (2020). Conversational Receptiveness: Improving Engagement with Opposing Views. OBHDP.

**Examples**

```
## Not run:
data("phone_offers")

receptiveness(phone_offers$message)

## End(Not run)
```

---

<code>receptive_polite</code>	<i>Pre-Trained Receptiveness Data</i>
-------------------------------	---------------------------------------

---

**Description**

A dataset to train a model for detecting conversational receptiveness.

**Usage**

```
receptive_polite
```

**Format**

Pre-calculated politeness features for the `receptive_train` dataset

---

<code>receptive_train</code>	<i>Pre-Trained Receptiveness Data</i>
------------------------------	---------------------------------------

---

**Description**

A dataset to train a model for detecting conversational receptiveness.

**Usage**

```
receptive_train
```

**Format**

A data frame with 2860 rows and 2 variables:

**text** character written response about policy disagreement

**receptive** numeric standardized average of annotator ratings for "receptiveness"

Primarily for use within the `receptiveness()` function. The data was compiled from Studies 1 and 4 of the original paper, as well as an unpublished study with a very similar design, in which text responses were rated by disagreeing others.

**Source**

Yeomans, M., Minson, J., Collins, H., Chen, F. & Gino, F. (2020).  
"Conversational Receptiveness: Improving Engagement with Opposing Views"  
<https://osf.io/2n59b/>

---

uk2us

*UK to US Conversion dictionary***Description**

For internal use only. This dataset contains a quanteda dictionary for converting UK words to US words. The models in this package were all trained on US English.

**Usage**

uk2us

**Format**

A quanteda dictionary with named entries. Names are the US version, and entries are the UK version.

**Source**

Borrowed from the quanteda.dictionaries package on github (from user kbenoit)

# Index

## \* datasets

bowl\_offers, 2  
feature\_table, 3  
hedge\_list, 4  
negative\_list, 5  
phone\_offers, 5  
polite\_dicts, 10  
positive\_list, 11  
receptive\_polite, 12  
receptive\_train, 12  
uk2us, 13

bowl\_offers, 2

feature\_table, 3, 6  
findPoliteTexts, 3

hedge\_list, 4

negative\_list, 5

phone\_offers, 5  
polite\_dicts, 10  
politeness, 3, 6, 8, 9  
politenessPlot, 7  
politenessProjection, 9  
positive\_list, 11

receptive\_polite, 12  
receptive\_train, 12  
receptiveness, 11

spacyr, 11

uk2us, 13