

Package ‘rcheology’

March 18, 2022

Version 4.1.3.0
Title Data on Base Packages for Current and Previous Versions of R
Description Provides a dataset of functions in all base packages of R versions 1.0.1 onwards.
License CC0
URL <https://github.com/hughjonesd/rcheology>
BugReports <https://github.com/hughjonesd/rcheology/issues>
Depends R(>= 2.10)
Encoding UTF-8
LazyData true
ByteCompile true
RoxygenNote 7.1.1
NeedsCompilation no
Author David Hugh-Jones [aut, cre]
Maintainer David Hugh-Jones <davidhughjones@gmail.com>
Repository CRAN
Date/Publication 2022-03-18 13:10:02 UTC

R topics documented:

rcheology-package	2
fun_changed	3
rcheology	3
Rversions	4
Index	5

rcheology-package

Data on base packages from current and previous versions of R

Description

rcheology is a data package providing two data frames:

Details

- [rcheology](#) lists objects in all versions of R from 1.0.1 onwards.
- [Rversions](#) lists R versions and their release dates. NB: For a more complete and "canonical" solution, see the [rversions](#) package.

The version of the rcheology package reflects the latest R version to be included in the data, e.g. 3.5.1.x contains data up to and including R 3.5.1.

An online app for data exploration is available at <https://hughjonesd.shinyapps.io/rcheology/>.

Where the data comes from:

Versions 4.0.0 and up are installed from the [CRAN apt repositories for Ubuntu Bionic](#).

Versions 3.0.1 to 3.6.3 are installed from the [CRAN apt repositories for Ubuntu Trusty Tahr](#).
Version 3.5.0 and up use a [special repository](#).

Versions 2.5.1 to 3.0.0 are built from source on [Ubuntu Lucid Lynx](#).

Versions 1.2.3 to 2.4.1 are mostly built from source on [Debian Sarge](#).

Versions 1.0.1 to 1.2.2 (and a couple of later versions) are built from source on [Debian Woody](#).

Results are found from running `ls` on all installed packages from a minimal installation. Recommended packages are not included.

The `Rversions` data frame lists versions of R and release dates.

Limitations

- Functions not built on the relevant platform - e.g. Windows functions - are not included.
- Because data is collected using the original R version, it is subject to changes in the way R works. For example, before 2.5.0, `args()` didn't work on Primitive functions, so those functions have no value in the `args` column.
- I have failed to build `tccltk` on R versions 1.0.1-1.4.1 and 1.7.0/1, so there's no `tccltk` data for these versions. If you can help, get in touch.

fun_changed	<i>Check if a core R function changed between R versions</i>
-------------	--

Description

Check if a core R function changed between R versions

Usage

```
fun_changed(fn, from = NULL, to = NULL, package = NULL)
```

Arguments

fn	Character name of a function in a core R package.
from	Minimum R version (optional).
to	Maximum R version (optional).
package	Name of the package (optional).

Value

0 if there was no change. 1 if the function's arguments changed. 2 if the function was not present in all versions. If the function can't be found or exists in multiple packages, throws an error.

Examples

```
fun_changed("debugonce")

fun_changed("debugonce", "3.4.0", "3.4.3")
fun_changed("debugonce", "3.3.0", "3.4.3")
```

rcheology	<i>Data on objects from current and previous versions of R</i>
-----------	--

Description

A data frame with every function (and other object) in versions of R from 1.0.1 onwards. Variables are:

- package: package the object comes from
- name: name of the object
- Rversion: version of R as major.minor.patch
- type: Result of calling `typeof()` on the object
- class: `class()` of the object, separated by slashes if there are multiple classes.

- `exported`: TRUE if the object name was found in `getNamespaceExports()`. True for anything in the "base" package. NA if the package does not have a namespace (e.g. "datasets" in early versions).
- `generic`: TRUE if the object is an S4 generic according to `methods::isGeneric()`
- `args`: the arguments of the function, or NA for non-functions

Rversions

Previous R versions with dates

Description

A data frame with 2 variables:

- `Rversion`: version of R as `major.minor.patch`
- `date`: date of release

Details

This goes back to 0.x releases. For 2.15.1-w, see [here](#).

Index

`args()`, [2](#)

`class()`, [3](#)

`fun_changed`, [3](#)

`getNamespaceExports()`, [4](#)

`methods::isGeneric()`, [4](#)

`rcheology`, [2](#), [3](#)

`rcheology-package`, [2](#)

`Rversions`, [2](#), [4](#)

`typeof()`, [3](#)