

# Package ‘rdryad’

June 25, 2020

**Type** Package

**Title** Access for Dryad Web Services

**Description** Interface to the Dryad “Solr” API, their “OAI-PMH” service, and fetch datasets. Dryad (<<https://datadryad.org/>>) is a curated host of data underlying scientific publications.

**Version** 1.0.0

**License** MIT + file LICENSE

**URL** <https://docs.ropensci.org/rdryad>,  
<https://github.com/ropensci/rdryad>

**BugReports** <https://github.com/ropensci/rdryad/issues>

**Encoding** UTF-8

**Language** en-US

**Imports** crul, curl, tibble, hoardr, zip, jsonlite, mime

**Suggests** testthat, vcr

**RoxygenNote** 7.1.0

**NeedsCompilation** no

**Author** Karthik Ram [aut] (<<https://orcid.org/0000-0002-0233-1757>>),  
Scott Chamberlain [aut, cre] (<<https://orcid.org/0000-0003-1444-9135>>),  
Carl Boettiger [aut] (<<https://orcid.org/0000-0002-1642-628X>>)

**Maintainer** Scott Chamberlain <[myrmecocystus@gmail.com](mailto:myrmecocystus@gmail.com)>

**Repository** CRAN

**Date/Publication** 2020-06-25 06:00:02 UTC

## R topics documented:

rdryad-package . . . . .	2
dryad_dataset . . . . .	3
dryad_datasets . . . . .	3
dryad_dataset_versions . . . . .	4

dryad_download . . . . .	5
dryad_files . . . . .	6
dryad_files_download . . . . .	6
versions . . . . .	7

<b>Index</b>	<b>9</b>
--------------	----------

---

rdryad-package	<i>Interface to the Dryad Web services</i>
----------------	--

---

## Description

Includes access to Dryad's Solr API, OAI-PMH service, and part of their REST API.

## Package API

The functions match the three major sets of Dryad API routes for datasets, files and versions.

Datasets:

- [dryad\\_dataset\(\)](#)
- [dryad\\_datasets\(\)](#)
- [dryad\\_dataset\\_versions\(\)](#)

Files:

- [dryad\\_files\(\)](#)
- [dryad\\_files\\_download\(\)](#)

Versions:

- [dryad\\_versions\(\)](#)
- [dryad\\_versions\\_files\(\)](#)
- [dryad\\_versions\\_download\(\)](#)

## Defunct

The Dryad Solr API is no longer being updated, so the functions that used to work with it are all defunct, see [solr-defunct](#)

The Dryad OAI-PMH service is no longer being updated, so the functions that used to work with it are all defunct, see [oai-defunct](#)

More defunct functions:

- [dryad\\_metadata\(\)](#)
- [dryad\\_package\\_dois\(\)](#)
- [handle2doi\(\)](#)
- [doi2handle\(\)](#)
- [dryad\\_files\(\)](#)
- [dryad\\_fetch\(\)](#) - use instead [dryad\\_files\\_download\(\)](#) or [dryad\\_versions\\_download\(\)](#)

---

dryad_dataset	<i>Get datasets by DOI(s)</i>
---------------	-------------------------------

---

**Description**

Get datasets by DOI(s)

**Usage**

```
dryad_dataset(dois, ...)
```

**Arguments**

`dois` (character) one or more DOIs, required  
`...` Further args passed on to [crul::verb-GET](#)

**Value**

a list of lists, each named by the input DOI

**See Also**

Other dryad-datasets: [dryad\\_dataset\\_versions\(\)](#), [dryad\\_datasets\(\)](#)

**Examples**

```
## Not run:  
dryad_dataset(doi = "10.5061/dryad.f385721n")  
dois <- c("10.5061/dryad.f385721n", "10.5061/dryad.7ct1n", "10.5061/dryad.1g626")  
dryad_dataset(dois = dois)  
  
## End(Not run)
```

---

dryad_datasets	<i>List datasets</i>
----------------	----------------------

---

**Description**

List datasets

**Usage**

```
dryad_datasets(...)
```

**Arguments**

`...` Further args passed on to [crul::verb-GET](#)

**Value**

a tibble

**See Also**

Other dryad-datasets: [dryad\\_dataset\\_versions\(\)](#), [dryad\\_dataset\(\)](#)

**Examples**

```
## Not run:  
(x <- dryad_datasets())  
x$meta  
x$links  
x$data  
  
## End(Not run)
```

---

`dryad_dataset_versions`

*Get dataset versions by DOI(s)*

---

**Description**

Get dataset versions by DOI(s)

**Usage**

```
dryad_dataset_versions(dois, ...)
```

**Arguments**

<code>dois</code>	(character) one or more DOIs, required
<code>...</code>	Further args passed on to <a href="#">crul::verb-GET</a>

**Value**

a list of lists, each named by the input DOI

**See Also**

Other dryad-datasets: [dryad\\_datasets\(\)](#), [dryad\\_dataset\(\)](#)

**Examples**

```
## Not run:
x = dryad_dataset_versions(dois = "10.5061/dryad.f385721n")
x
dois <- c("10.5061/dryad.f385721n", "10.5061/dryad.7ct1n", "10.5061/dryad.1g626")
dryad_dataset_versions(dois = dois)

## End(Not run)
```

---

<code>dryad_download</code>	<code>dryad_download</code>
-----------------------------	-----------------------------

---

**Description**

Download datasets by their DOI(s)

**Usage**

```
dryad_download(dois, ...)
```

**Arguments**

<code>dois</code>	(character) one or more DOIs, required
<code>...</code>	Further args passed on to <a href="#">crul::verb-GET</a>

**Value**

file path for the file

**Examples**

```
## Not run:
dryad_download(dois = "10.5061/dryad.f385721n")
dois <- c("10.5061/dryad.f385721n", "10.5061/dryad.7ct1n", "10.5061/dryad.1g626")
dryad_download(dois = dois)

## End(Not run)
```

`dryad_files`            *Get metadata information about a file*

---

**Description**

Get metadata information about a file

**Usage**

```
dryad_files(ids, ...)
```

**Arguments**

`ids`            (numeric) one or more file ids, required  
`...`            Further args passed on to [crul::verb-GET](#)

**Value**

a list of lists, each named by the input DOI

**See Also**

Other dryad-files: [dryad\\_files\\_download\(\)](#)

**Examples**

```
## Not run:  
dryad_files(ids = 61859)  
dryad_files(ids = 61858)  
dryad_files(ids = c(61858, 61859))  
  
## End(Not run)
```

---

`dryad_files_download`    *Download a specific file*

---

**Description**

Download a specific file

**Usage**

```
dryad_files_download(ids, ...)
```

**Arguments**

ids (numeric) one or more file ids, required  
 ... Further args passed on to [crul::verb-GET](#)

**Value**

a list of lists, each named by the input DOI

**Note**

there's no use of cached files here because we can't determine what the file path will be before making the request, which requires knowing what the data type the file will be

**See Also**

Other dryad-files: [dryad\\_files\(\)](#)

**Examples**

```
## Not run:
dryad_files_download(ids = 61858)
dryad_files_download(ids = 61859)

## End(Not run)
```

---

 versions

---

*Get a dataset version by version ID*


---

**Description**

Get a dataset version by version ID

**Usage**

```
dryad_versions(ids, ...)
dryad_versions_files(ids, ...)
dryad_versions_download(ids, ...)
```

**Arguments**

ids (numeric/integer) one or more version ids, required  
 ... Further args passed on to [crul::verb-GET](#)

**Details**

`dryad_versions()` and `dryad_versions_files()` use async http requests, while `dryad_versions_download()` does not use async

**Value**

a list of lists, each named by the input DOI

**Examples**

```
## Not run:  
dryad_versions(ids = 18774)  
dryad_versions_files(ids = 18774)  
dryad_versions_download(ids = 18774)  
  
## End(Not run)
```



# Index

`curl::verb-GET`, 3–7

`doi2handle()`, 2

`dryad_dataset`, 3, 4

`dryad_dataset()`, 2

`dryad_dataset_versions`, 3, 4, 4

`dryad_dataset_versions()`, 2

`dryad_datasets`, 3, 3, 4

`dryad_datasets()`, 2

`dryad_download`, 5

`dryad_fetch()`, 2

`dryad_files`, 6, 7

`dryad_files()`, 2

`dryad_files_download`, 6, 6

`dryad_files_download()`, 2

`dryad_metadata()`, 2

`dryad_package_dois()`, 2

`dryad_versions (versions)`, 7

`dryad_versions()`, 2

`dryad_versions_download (versions)`, 7

`dryad_versions_download()`, 2

`dryad_versions_files (versions)`, 7

`dryad_versions_files()`, 2

`handle2doi()`, 2

`oai-defunct`, 2

`rdryad (rdryad-package)`, 2

`rdryad-package`, 2

`solr-defunct`, 2

`versions`, 7