

Package ‘robmed’

March 17, 2022

Type Package

Title (Robust) Mediation Analysis

Version 0.10.1

Date 2022-03-17

Depends R (>= 3.5.0), ggplot2 (>= 3.3.0), robustbase (>= 0.92-7)

Imports boot (>= 1.3-20), grid, methods, quantreg (>= 5.36), sn (>= 1.5-4), utils

Suggests knitr, testthat

Description Perform mediation analysis via a (fast and robust) bootstrap test.

License GPL (>= 2)

URL <https://github.com/aalfons/robmed>

BugReports <https://github.com/aalfons/robmed/issues>

LazyData yes

VignetteBuilder knitr

Author Andreas Alfons [aut, cre] (<<https://orcid.org/0000-0002-2513-3788>>),
Nufer Y. Ates [ctb] (<<https://orcid.org/0000-0003-4572-4101>>, provided
the BSG2014 data)

Maintainer Andreas Alfons <aalfons@ese.eur.nl>

Encoding UTF-8

RoxygenNote 7.1.2

NeedsCompilation no

Repository CRAN

Date/Publication 2022-03-17 14:20:02 UTC

R topics documented:

| | |
|--------------------------|---|
| robmed-package | 2 |
| boot_samples | 4 |
| BSG2014 | 5 |

| | |
|----------------------------------|----|
| ci_plot | 8 |
| coef.test_mediation | 10 |
| confint.test_mediation | 12 |
| cov_control | 13 |
| cov_Huber | 14 |
| cov_ML | 16 |
| density_plot | 17 |
| ellipse_plot | 18 |
| fit_mediation | 21 |
| m | 25 |
| plot-methods | 26 |
| p_value | 28 |
| reg_control | 30 |
| retest | 31 |
| setup_ci_plot | 33 |
| setup_density_plot | 35 |
| setup_ellipse_plot | 37 |
| setup_weight_plot | 40 |
| summary.test_mediation | 42 |
| test_mediation | 43 |
| weights.cov_Huber | 49 |
| weight_plot | 50 |

Index 53

| | |
|----------------|------------------------------------|
| robmed-package | <i>(Robust) Mediation Analysis</i> |
|----------------|------------------------------------|

Description

Perform mediation analysis via a (fast and robust) bootstrap test.

Details

The DESCRIPTION file:

```

Package:      robmed
Type:         Package
Title:        (Robust) Mediation Analysis
Version:      0.10.1
Date:         2022-03-17
Depends:      R (>= 3.5.0), ggplot2 (>= 3.3.0), robustbase (>= 0.92-7)
Imports:      boot (>= 1.3-20), grid, methods, quantreg (>= 5.36), sn (>= 1.5-4), utils
Suggests:     knitr, testthat
Description:  Perform mediation analysis via a (fast and robust) bootstrap test.
License:      GPL (>= 2)
URL:          https://github.com/aalfons/robmed
BugReports:   https://github.com/aalfons/robmed/issues

```

```

LazyData:      yes
VignetteBuilder: knitr
Authors@R:     c(person("Andreas", "Alfons", email = "alfons@ese.eur.nl", role = c("aut", "cre"), comment = c(ORCID =
Author:        Andreas Alfons [aut, cre] (<https://orcid.org/0000-0002-2513-3788>), Nufer Y. Ates [ctb] (<https://orcid.o
Maintainer:    Andreas Alfons <alfons@ese.eur.nl>
Encoding:      UTF-8
RoxygenNote:   7.1.2

```

Index of help topics:

```

BSG2014          Business simulation game data
boot_samples     Draw bootstrap samples
ci_plot          Dot plot with confidence intervals
coef.test_mediation Coefficients in (robust) mediation analysis
confint.test_mediation Confidence intervals from (robust) mediation
                    analysis
cov_Huber        Huber M-estimator of location and scatter
cov_ML           Maximum likelihood estimator of mean vector and
                    covariance matrix
cov_control      Tuning parameters for Huber M-estimation of
                    location and scatter
density_plot     Density plot of the indirect effect(s)
ellipse_plot     Diagnostic plot with a tolerance ellipse
fit_mediation    (Robustly) fit a mediation model
m               Create an object of hypothesized mediators or
                    control variables
p_value          p-Values from (robust) mediation analysis
plot-methods     Plot (robust) mediation analysis results
reg_control      Tuning parameters for MM-regression
retest          Retest for mediation
robmed-package   (Robust) Mediation Analysis
setup_ci_plot    Set up information for a dot plot with
                    confidence intervals
setup_density_plot Set up information for a density plot of the
                    indirect effect(s)
setup_ellipse_plot Set up a diagnostic plot with a tolerance
                    ellipse
setup_weight_plot Set up a diagnostic plot of robust regression
                    weights
summary.test_mediation Summary of results from (robust) mediation
                    analysis
test_mediation   (Robust) mediation analysis
weight_plot      Diagnostic plot of robust regression weights
weights.cov_Huber Robustness weights of Huber M-estimation of
                    location and scatter

```

Author(s)

Andreas Alfons [aut, cre] (<<https://orcid.org/0000-0002-2513-3788>>), Nufer Y. Ates [ctb] (<<https://orcid.org/0000-0003-4572-4101>>), provided the BSG2014 data)

Maintainer: Andreas Alfons <alfons@ese.eur.nl>

References

Alfons, A., Ates, N.Y. and Groenen, P.J.F. (2021) A robust bootstrap test for mediation analysis. *Organizational Research Methods*, doi: 10.1177/1094428121999096.

| | |
|--------------|-------------------------------|
| boot_samples | <i>Draw bootstrap samples</i> |
|--------------|-------------------------------|

Description

Draw bootstrap samples to be used for (fast-and-robust) bootstrap tests for mediation analysis. Note that this function is intended for use in simulation studies, it is not expected to be called by the user.

Usage

```
boot_samples(n, R)
```

Arguments

| | |
|---|--|
| n | an integer giving the number of observations in the original data set. |
| R | an integer giving the number of bootstrap samples to be generated. |

Value

An object of class "boot_samples" with the following components:

| | |
|---------|--|
| indices | an integer matrix in which each column contains the indices of the corresponding bootstrap sample. |
| seed | the state of the random number generator before the bootstrap samples were drawn |

Author(s)

Andreas Alfons

See Also

[test_mediation\(\)](#)

Examples

```
# control parameters
n <- 100
a <- b <- c <- 0.4

# generate data
set.seed(20200309)
x <- rnorm(n)
m <- a * x + rnorm(n)
y <- b * m + c * x + rnorm(n)
simulated_data <- data.frame(x, y, m)

# perform bootstrap tests
indices <- boot_samples(n, R = 5000)
robust_boot <- test_mediation(simulated_data,
                             x = "x", y = "y", m = "m",
                             robust = TRUE,
                             indices = indices)
summary(robust_boot)
standard_boot <- test_mediation(simulated_data,
                                x = "x", y = "y", m = "m",
                                robust = FALSE,
                                indices = indices)
summary(standard_boot)
```

BSG2014

Business simulation game data

Description

The data were collected from 354 senior business administration students during a business simulation game at a Western European University.

The game was played for a total of 12 rounds (i.e., two separate games of 6 rounds) as part of the capstone strategy class. Students were randomly assigned to teams of four, and surveyed in three waves: prior to the first game, in between the two games, and after the second game (with different variables being surveyed in the different waves).

The 354 students formed 92 teams, and the responses of individual students were aggregated to the team level. Leaving out teams with less than 50 percent response rate yields $n = 89$ teams. Only a small subset of the collected variables are included here.

Usage

```
data("BSG2014")
```

Format

A data frame with 89 observations on the following 13 variables.

ProcessConflict Process conflict was operationalized with the three-item scale of Jehn (1995) and responses were aggregated. Process conflict was measured in the second survey (between the two games).

SharedExperience Teams were randomly formed, no prior shared group experience is expected and shared group experience and training is developed during the first game for the second game. The team's score on the first game, which is determined by objective performance measures, is used as a proxy for the level of shared group experience and training.

TaskConflict Task conflict was operationalized with the intra-group conflict scale of Jehn (1995). Five items on the presence of conflict were rated on a 5-point Likert scale (1 = none, 5 = a lot) and aggregated. Task conflict was measured in the second survey (between the two games).

TeamCommitment Team commitment was measured by four items based on Mowday, Steers & Porter (1979) and responses were aggregated. Team commitment was measured in the third survey (after the second game).

TeamPerformance Team performance in the second game was measured subjectively by the team members' perceptions of the team's functioning, using aggregated responses to Hackman's (1986) Likert scale items. Subjective team performance was measured in the third survey (after the second game).

TMS Transactive memory systems (TMS) are defined as shared systems that people in relationships develop for encoding, storing, and retrieving information about different substantive domains. TMS was operationalized with Lewis' (2003) 15-item scale that measures the three sub-dimensions of TMS (credibility, specialization and coordination). Team members responded on a 5-point scale (1 = strongly disagree, 5 = strongly agree). Following Lewis (2003), the three sub dimensions were aggregated to form the TMS construct. TMS was measured in the second survey (between the two games).

ValueDiversity Value diversity was operationalized with the short version of Schwartz's Value Survey (SVS) to measure team members' individual values (Lindeman & Verkasalo, 2005). The responses were aggregated with the average of the coefficient of variations of each value dimension among team members. Value diversity was measured in the first survey (before the first game).

ProceduralJustice Procedural justice was measured by the intra-unit procedural justice climate items of Li & Cropanzano (2009). Respondents indicated the extent to which they agree or disagree with these items on a 5-point Likert scale (1 = strongly disagree, 5 = strongly agree), and the items were aggregated to the team level. Procedural justice was measured in the third survey (after the second game).

InteractionalJustice Interactional justice was measured by the intra-unit interactional justice climate items of Li & Cropanzano (2009). Respondents indicated the extent to which they agree or disagree with these items on a 5-point Likert scale (1 = strongly disagree, 5 = strongly agree), and the items were aggregated to the team level. Interactional justice was measured in the third survey (after the second game).

SharedLeadership Shared leadership was measured following Carson, Tesluk & Marrone (2007). Every team member assessed each of their peers on a 5-point Likert scale (1 = not at all, 5 = to a very great extent) on the question of 'To what degree does your team rely on this individual for leadership?'. To operationalize shared leadership, we then summed all ratings of each

other's leadership and divide it by the total number of possible relationships among team members. Shared leadership was measured in the second survey (between the two games).

AgeDiversity Following Harrison & Klein (2007), age diversity was operationalized with the coefficient of variation of the team members' ages.

GenderDiversity Gender diversity was measured with Blau's index, $1 - \sum_i p_i^2$, where p_i is the proportion of team members in the i -th category (Blau, 1977).

TeamScore The team performance scores on the second game were computed at the end of the simulation through a mix of five objective performance measures: return on equity, earnings-per-share, stock price, credit rating, and image rating. The scores are automatically computed by the simulation game software, and scores ranged from 49 to 110. See Mathieu & Rapp (2009) for more information. The scores were communicated to the teams only after the third survey.

References

- Blau, P.M. (1977) *Inequality and Heterogeneity: A Primitive Theory of Social Structure*. New York, NY: Free Press.
- Carson, J.B., Tesluk, P.E. and Marrone, J.A. (2007) Shared Leadership in Teams: An Investigation of Antecedent Conditions and Performance. *Academy of Management Journal*, **50**(5), 1217–1234.
- Hackman, J.R. (1986) The Psychology of Self-Management in Organizations. In Pallack, M.S and Perloff, R.O. (Eds.), *Psychology and Work: Productivity, Change, and Employment*, 89–136. Washington, DC: American Psychological Association.
- Harrison, D.A. and Klein, K.J. (2007) What's the Difference? Diversity Constructs as Separation, Variety, or Disparity in Organizations. *Academy of Management Review*, **32**(4): 1199–1228.
- Jehn, K.A. (1995) A Multi-Method Examination of the Benefits and Detriments of Intra-Group Conflict. *Administrative Science Quarterly*, **40**(2), 256–285.
- Lewis, K. (2003) Measuring Transactive Memory Systems in the Field: Scale Development and Validation. *Journal of Applied Psychology*, **88**(4), 587–604.
- Li, A. and Cropanzano, R. (2009) Fairness at the Group Level: Justice Climate and Intraunit Justice Climate. *Journal of Management*, **35**(3), 564–599.
- Lindeman, M. and Verkasalo, M. (2005) Measuring Values With the Short Schwartz's Value Survey. *Journal of Personality Assessment*, **85**(2), 170–178.
- Mathieu, J.E. and Rapp, T.L. (2009). Laying the Foundation for Successful Team Performance Trajectories: The Roles of Team Charters and Performance Strategies. *Journal of Applied Psychology*, **94**(1), 90–103.
- Mowday, R.T., Steers, R.M. and Porter, L.W. (1979) The Measurement of Organizational Commitment. *Journal of Vocational Behavior*, **14**(2), 224–47.

Examples

```
data("BSG2014")
summary(BSG2014)

# scatterplot matrix for the variables included in the
# illustrative mediation analysis
x <- "ValueDiversity"
```

```

y <- "TeamCommitment"
m <- "TaskConflict"
plot(BSG2014[, c(x, y, m)], pch = 21, bg = "black")

```

ci_plot

Dot plot with confidence intervals

Description

Produce a dot plot with confidence intervals of selected effects from (robust) mediation analysis. In addition to confidence intervals, p-values of the selected effects can be plotted as well.

Usage

```

ci_plot(object, ...)

## Default S3 method:
ci_plot(object, parm = c("direct", "indirect"), ...)

## S3 method for class 'boot_test_mediation'
ci_plot(
  object,
  parm = c("direct", "indirect"),
  type = c("boot", "data"),
  p_value = FALSE,
  digits = 4L,
  ...
)

## S3 method for class 'sobel_test_mediation'
ci_plot(
  object,
  parm = c("direct", "indirect"),
  level = 0.95,
  p_value = FALSE,
  ...
)

## S3 method for class 'list'
ci_plot(
  object,
  parm = c("direct", "indirect"),
  type = c("boot", "data"),
  level = 0.95,
  p_value = FALSE,
  digits = 4L,
  ...
)

```

```
)

## S3 method for class 'setup_ci_plot'
ci_plot(object, ...)
```

Arguments

| | |
|---------|---|
| object | an object inheriting from class " test_mediation " containing results from (robust) mediation analysis, or a list of such objects. |
| ... | additional arguments to be passed down. |
| parm | an integer, character or logical vector specifying which effects to include in the plot. In case of a character vector, possible values are "a", "b", "d" (only serial multiple mediator models), "total", "direct", and "indirect". The default is to include the direct and the indirect effect(s). |
| type | a character string specifying which point estimates and confidence intervals to plot: those based on the bootstrap distribution ("boot"; the default), or those based on the original data ("data"). If "boot", the confidence intervals of effects other than the indirect effect(s) are computed using a normal approximation (i.e., assuming a normal distribution of the corresponding effect with the standard deviation computed from the bootstrap replicates). If "data", the confidence intervals of effects other than the indirect effect(s) are computed via statistical theory based on the original data (e.g., based on a t-distribution if the coefficients are estimated via regression). Note that this is only relevant for mediation analysis via a bootstrap test, where the confidence interval of the indirect effect is always computed via a percentile-based method due to the asymmetry of its distribution. |
| p_value | a logical indicating whether to include dot plots of the p-values in addition to those with confidence intervals. The default is FALSE. |
| digits | an integer determining how many digits to compute for bootstrap p-values of the indirect effects (see p_value()). The default is to compute 4 digits after the comma. This is only relevant if <code>p_value = TRUE</code> . |
| level | numeric; the confidence level of the confidence intervals from Sobel's test. The default is to include 95% confidence intervals. Note that this is not used for bootstrap tests, as those require to specify the confidence level already in test_mediation() . |

Details

Methods first call [setup_ci_plot\(\)](#) to extract all necessary information to produce the plot, then the "setup_ci_plot" method is called to produce the plot.

Value

An object of class "[ggplot](#)".

Author(s)

Andreas Alfons

See Also

```
test_mediation(), setup_ci_plot()
density_plot(), ellipse_plot(), weight_plot(), plot()
```

Examples

```
data("BSG2014")

# run fast-and-robust bootstrap test
robust_boot <- test_mediation(BSG2014,
                             x = "ValueDiversity",
                             y = "TeamCommitment",
                             m = "TaskConflict",
                             robust = TRUE)

# create plot for robust bootstrap test
ci_plot(robust_boot)
ci_plot(robust_boot, color = "#00BFC4")

# run standard bootstrap test
standard_boot <- test_mediation(BSG2014,
                                x = "ValueDiversity",
                                y = "TeamCommitment",
                                m = "TaskConflict",
                                robust = FALSE)

# compare robust and standard tests
tests <- list(Standard = standard_boot, Robust = robust_boot)
ci_plot(tests)

# the plot can be customized in the usual way
ci_plot(tests) +
  geom_hline(yintercept = 0, color = "darkgrey") +
  coord_flip() + theme_bw() +
  labs(title = "Standard vs robust bootstrap test")
```

```
coef.test_mediation    Coefficients in (robust) mediation analysis
```

Description

Extract coefficients from models computed in (robust) mediation analysis.

Usage

```
## S3 method for class 'test_mediation'
coef(object, parm = NULL, ...)
```

```
## S3 method for class 'boot_test_mediation'
coef(object, parm = NULL, type = c("boot", "data"), ...)

## S3 method for class 'fit_mediation'
coef(object, parm = NULL, ...)
```

Arguments

| | |
|--------|---|
| object | an object inheriting from class <code>"test_mediation"</code> containing results from (robust) mediation analysis, or an object inheriting from class <code>"fit_mediation"</code> containing a (robust) mediation model fit. |
| parm | an integer, character or logical vector specifying the paths for which to extract coefficients, or NULL to extract all coefficients. In case of a character vector, possible values are <code>"a"</code> , <code>"b"</code> , <code>"d"</code> (only serial multiple mediator models), <code>"total"</code> , <code>"direct"</code> , and <code>"indirect"</code> . |
| ... | additional arguments are currently ignored. |
| type | a character string specifying whether to extract the means of the bootstrap distribution (<code>"boot"</code> ; the default), or the coefficient estimates based on the original data set (<code>"data"</code>). |

Value

A numeric vector containing the requested coefficients.

Author(s)

Andreas Alfons

See Also

`test_mediation()`, `fit_mediation()`, `confint()`, `p_value()`

Examples

```
data("BSG2014")

# fit robust mediation model and extract coefficients
fit <- fit_mediation(BSG2014,
  x = "ValueDiversity",
  y = "TeamCommitment",
  m = "TaskConflict")

coef(fit)

# run fast-and-robust bootstrap test and extract coefficients
test <- test_mediation(fit)
coef(test, type = "data") # from original sample
coef(test, type = "boot") # means of bootstrap replicates
```

confint.test_mediation

Confidence intervals from (robust) mediation analysis

Description

Extract or compute confidence intervals for effects in (robust) mediation analysis.

Usage

```
## S3 method for class 'boot_test_mediation'
confint(object, parm = NULL, level = NULL, type = c("boot", "data"), ...)

## S3 method for class 'sobel_test_mediation'
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

| | |
|--------|---|
| object | an object inheriting from class " <code>test_mediation</code> " containing results from (robust) mediation analysis. |
| parm | an integer, character or logical vector specifying the paths for which to extract or compute confidence intervals, or NULL to extract or compute confidence intervals for all coefficients. In case of a character vector, possible values are "a", "b", "d" (only serial multiple mediator models), "total", "direct", and "indirect". |
| level | for the " <code>boot_test_mediation</code> " method, this is ignored and the confidence level of the bootstrap confidence interval for the indirect effect is used. For the other methods, the confidence level of the confidence intervals to be computed. The default is to compute 95% confidence intervals. |
| type | a character string specifying how to compute the confidence interval of the effects other than the indirect effect(s). Possible values are "boot" (the default) to compute bootstrap confidence intervals using the normal approximation (i.e., to assume a normal distribution of the corresponding effect with the standard deviation computed from the bootstrap replicates), or "data" to compute confidence intervals via statistical theory based on the original data (e.g., based on a t-distribution if the coefficients are estimated via regression). Note that this is only relevant for mediation analysis via a bootstrap test, where the confidence interval of the indirect effect is always computed via a percentile-based method due to the asymmetry of its distribution. |
| ... | additional arguments are currently ignored. |

Value

A numeric matrix containing the requested confidence intervals.

Author(s)

Andreas Alfons

See Also[test_mediation\(\)](#), [coef\(\)](#), [p_value\(\)](#), [boot.ci\(\)](#)**Examples**

```
data("BSG2014")

# run fast-and-robust bootstrap test
robust_boot <- test_mediation(BSG2014,
                             x = "ValueDiversity",
                             y = "TeamCommitment",
                             m = "TaskConflict",
                             robust = TRUE)
confint(robust_boot, type = "boot")

# run standard bootstrap test
standard_boot <- test_mediation(BSG2014,
                                x = "ValueDiversity",
                                y = "TeamCommitment",
                                m = "TaskConflict",
                                robust = FALSE)
confint(standard_boot, type = "data")
```

cov_control

Tuning parameters for Huber M-estimation of location and scatter

Description

Obtain a list with tuning parameters for [cov_Huber\(\)](#).

Usage

```
cov_control(prob = 0.95, max_iterations = 200, tol = 1e-07)
```

Arguments

| | |
|----------------|--|
| prob | numeric; probability for the quantile of the χ^2 distribution to be used as cutoff point in the Huber weight function (defaults to 0.95). |
| max_iterations | an integer giving the maximum number of iterations in the iteratively reweighted algorithm. |
| tol | a small positive numeric value to be used to determine convergence of the iteratively reweighted algorithm. |

Value

A list with components corresponding to the arguments.

Author(s)

Andreas Alfons

References

Huber, P.J. (1981) *Robust statistics*. John Wiley & Sons.

See Also

[cov_Huber\(\)](#)

Examples

```
data("BSG2014")

# run bootstrap test after winsorization
ctrl <- cov_control(prob = 0.95)
test <- test_mediation(BSG2014,
                       x = "ValueDiversity",
                       y = "TeamCommitment",
                       m = "TaskConflict",
                       method = "covariance",
                       control = ctrl)

summary(test)
```

cov_Huber

Huber M-estimator of location and scatter

Description

Compute a Huber M-estimator of location and scatter, which is reasonably robust for a small number of variables.

Usage

```
cov_Huber(x, control = cov_control(...), ...)
```

Arguments

| | |
|---------|--|
| x | a numeric matrix or data frame. |
| control | a list of tuning parameters as generated by cov_control() . |
| ... | additional arguments can be used to specify tuning parameters directly instead of via control. |

Details

An iterative reweighting algorithm is used to compute the Huber M-estimator. The Huber weight function thereby corresponds to a convex optimization problem, resulting in a unique solution.

Value

An object of class "cov_Huber" with the following components:

| | |
|------------|---|
| center | a numeric vector containing the location vector estimate. |
| cov | a numeric matrix containing the scatter matrix estimate. |
| prob | numeric; probability for the quantile of the χ^2 distribution used as cutoff point in the Huber weight function. |
| weights | a numeric vector containing the relative robustness weights for the observations. |
| tau | numeric; correction for Fisher consistency under multivariate normal distributions. |
| converged | a logical indicating whether the iterative reweighting algorithm converged. |
| iterations | an integer giving the number of iterations required to obtain the solution. |

Author(s)

Andreas Alfons

References

Huber, P.J. (1981) *Robust statistics*. John Wiley & Sons.

Zu, J. and Yuan, K.-H. (2010) Local influence and robust procedures for mediation analysis. *Multivariate Behavioral Research*, **45**(1), 1–44.

See Also

[cov_control\(\)](#), [test_mediation\(\)](#), [fit_mediation\(\)](#)

Examples

```
data("BSG2014")

# define variables
x <- "ValueDiversity"
y <- "TeamCommitment"
m <- "TaskConflict"

# compute Huber M-estimator
cov_Huber(BSG2014[, c(x, y, m)])
```

| | |
|--------|--|
| cov_ML | <i>Maximum likelihood estimator of mean vector and covariance matrix</i> |
|--------|--|

Description

Compute the maximum likelihood estimator of the mean vector and the covariance matrix.

Usage

```
cov_ML(x, ...)
```

Arguments

| | |
|-----|---|
| x | a numeric matrix or data frame. |
| ... | additional arguments are currently ignored. |

Value

An object of class "cov_ML" with the following components:

| | |
|--------|---|
| center | a numeric vector containing the mean vector estimate. |
| cov | a numeric matrix containing the covariance matrix estimate. |
| n | an integer giving the number of observations. |

Author(s)

Andreas Alfons

References

Zu, J. and Yuan, K.-H. (2010) Local influence and robust procedures for mediation analysis. *Multivariate Behavioral Research*, **45**(1), 1–44.

See Also

[test_mediation\(\)](#), [fit_mediation\(\)](#)

Examples

```
data("BSG2014")

# define variables
x <- "ValueDiversity"
y <- "TeamCommitment"
m <- "TaskConflict"

# compute Huber M-estimator
cov_ML(BSG2014[, c(x, y, m)])
```

| | |
|--------------|---|
| density_plot | <i>Density plot of the indirect effect(s)</i> |
|--------------|---|

Description

Produce a density plot of the indirect effect(s) from (robust) mediation analysis. In addition to the density, a vertical line representing the point estimate and a shaded area representing the confidence interval are drawn.

Usage

```
density_plot(object, ...)

## Default S3 method:
density_plot(object, ...)

## S3 method for class 'sobel_test_mediation'
density_plot(object, grid = NULL, level = 0.95, ...)

## S3 method for class 'list'
density_plot(object, grid = NULL, level = 0.95, ...)

## S3 method for class 'setup_density_plot'
density_plot(object, ...)
```

Arguments

| | |
|--------|---|
| object | an object inheriting from class " test_mediation " containing results from (robust) mediation analysis, or a list of such objects. |
| ... | additional arguments to be passed down. |
| grid | an optional numeric vector containing the values at which to evaluate the assumed normal density from Sobel's test. The default is to take 512 equally spaced points between the estimated indirect effect \pm three times the standard error according to Sobel's formula. |
| level | numeric; the confidence level of the confidence intervals from Sobel's test. The default is to include 95% confidence intervals. Note that this is not used for bootstrap tests, as those require to specify the confidence level already in test_mediation() . |

Details

Methods first call [setup_density_plot\(\)](#) to extract all necessary information to produce the plot, then the "setup_density_plot" method is called to produce the plot.

Value

An object of class "[ggplot](#)".

Author(s)

Andreas Alfons

See Also

```
test_mediation(), setup_density_plot()
ci_plot(), ellipse_plot(), weight_plot(), plot()
```

Examples

```
data("BSG2014")

# run fast-and-robust bootstrap test
robust_boot <- test_mediation(BSG2014,
                             x = "ValueDiversity",
                             y = "TeamCommitment",
                             m = "TaskConflict",
                             robust = TRUE)

# create plot for robust bootstrap test
density_plot(robust_boot)
density_plot(robust_boot, color = "#00BFC4", fill = "#00BFC4")

# run standard bootstrap test
standard_boot <- test_mediation(BSG2014,
                               x = "ValueDiversity",
                               y = "TeamCommitment",
                               m = "TaskConflict",
                               robust = FALSE)

# compare robust and standard tests
tests <- list(Standard = standard_boot, Robust = robust_boot)
density_plot(tests)

# the plot can be customized in the usual way
density_plot(tests) + theme_bw() +
  labs(title = "Standard vs robust bootstrap test")
```

ellipse_plot

Diagnostic plot with a tolerance ellipse

Description

Produce a scatter plot of two variables used in (robust) mediation analysis together with a tolerance ellipse. Exploiting the relationship between the regression coefficients and the covariance matrix, that tolerance ellipse illustrates how well the regression results represent the data. In addition, a line that visualizes the estimated regression coefficient is added when relevant.

Usage

```

ellipse_plot(object, ...)

## Default S3 method:
ellipse_plot(
  object,
  horizontal = NULL,
  vertical = NULL,
  partial = FALSE,
  level = 0.975,
  npoints = 100,
  ...
)

## S3 method for class 'setup_ellipse_plot'
ellipse_plot(object, ...)

```

Arguments

| | |
|------------|---|
| object | an object inheriting from class <code>"fit_mediation"</code> or <code>"test_mediation"</code> containing results from (robust) mediation analysis, or a list of such objects. |
| ... | additional arguments to be passed down. |
| horizontal | a character string specifying the variable to be plotted on the horizontal axis. If the dependent variable is chosen for the vertical axis, a hypothesized mediator or an independent variable must be selected for the horizontal axis. If a hypothesized mediator is chosen for the vertical axis, an independent variable must be selected for the horizontal axis (in case of a serial multiple mediator model, a hypothesized mediator occurring earlier in the sequence is also allowed). The default is to plot the first independent variable on the horizontal axis. |
| vertical | a character string specifying the variable to be plotted on the vertical axis: the dependent variable or a hypothesized mediator. The default is to plot the first hypothesized mediator on the vertical axis. |
| partial | a logical indicating whether the vertical axis should display the observed values of the selected variable (FALSE), or the partial residuals with respect to the variable on the horizontal axis (TRUE). The latter allows to display the corresponding regression coefficient by a line. |
| level | numeric; the confidence level of the tolerance ellipse. It gives the percentage of observations that are expected to lie within the ellipse under the assumption of a normal distribution, and therefore it controls the size of the ellipse. The default is such that the ellipse is expected to contain 97.5% of the observations. |
| npoints | the number of grid points used to evaluate and draw the ellipse. The default is to use 100 grid points. |

Details

A line to visualize the corresponding regression coefficient is added if `partial = TRUE`, or in case of a simple mediation model (without control variables) when the hypothesized mediator is plotted

on the vertical axis and the independent variable is plotted on the horizontal axis.

For robust estimation methods that return outlyingness weights for each data point, those weights are visualized by coloring the points on a grey scale. If a list of objects has been supplied and there are multiple objects from such robust methods, each method is placed in a separate panel.

Methods first call `setup_ellipse_plot()` to extract all necessary information to produce the plot, then the "setup_ellipse_plot" method is called to produce the plot.

Value

An object of class "ggplot".

Author(s)

Andreas Alfons

See Also

`fit_mediation()`, `test_mediation()`, `setup_ellipse_plot()`
`ci_plot()`, `density_plot()`, `weight_plot()`, `plot()`

Examples

```
data("BSG2014")

# run fast-and-robust bootstrap test
robust_boot <- test_mediation(BSG2014,
                             x = "ValueDiversity",
                             y = "TeamCommitment",
                             m = "TaskConflict",
                             robust = TRUE)

# create plot for robust bootstrap test
ellipse_plot(robust_boot)

# original data and partial residuals
ellipse_plot(robust_boot, horizontal = "TaskConflict",
             vertical = "TeamCommitment")
ellipse_plot(robust_boot, horizontal = "TaskConflict",
             vertical = "TeamCommitment", partial = TRUE)

# run standard bootstrap test
standard_boot <- test_mediation(BSG2014,
                                x = "ValueDiversity",
                                y = "TeamCommitment",
                                m = "TaskConflict",
                                robust = FALSE)

# compare robust and standard tests
tests <- list(OLS = standard_boot, Robust = robust_boot)
ellipse_plot(tests)
```

```
# the plot can be customized in the usual way
ellipse_plot(tests) + theme_bw() +
  labs(title = "OLS vs robust estimation")
```

| | |
|---------------|---|
| fit_mediation | <i>(Robustly) fit a mediation model</i> |
|---------------|---|

Description

(Robustly) estimate the effects in a mediation model.

Usage

```
fit_mediation(object, ...)

## S3 method for class 'formula'
fit_mediation(formula, data, ...)

## Default S3 method:
fit_mediation(
  object,
  x,
  y,
  m,
  covariates = NULL,
  method = c("regression", "covariance"),
  robust = TRUE,
  family = "gaussian",
  model = c("parallel", "serial"),
  contrast = FALSE,
  fit_yx = TRUE,
  control = NULL,
  ...
)
```

Arguments

| | |
|---------|--|
| object | the first argument will determine the method of the generic function to be dispatched. For the default method, this should be a data frame containing the variables. |
| ... | additional arguments to be passed down. For the default method, this can be used to specify tuning parameters directly instead of via control. |
| formula | an object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted. Hypothesized mediator variables should be wrapped in a call to <code>m()</code> (see examples), and any optional control variables should be wrapped in a call to <code>covariates()</code> . |

| | |
|------------|--|
| data | for the formula method, a data frame containing the variables. |
| x | a character, integer or logical vector specifying the columns of object containing the independent variables of interest. |
| y | a character string, an integer or a logical vector specifying the column of object containing the dependent variable. |
| m | a character, integer or logical vector specifying the columns of object containing the hypothesized mediator variables. |
| covariates | optional; a character, integer or logical vector specifying the columns of object containing additional covariates to be used as control variables. |
| method | a character string specifying the method of estimation. Possible values are "regression" (the default) to estimate the effects via regressions, or "covariance" to estimate the effects via the covariance matrix. Note that the effects are always estimated via regressions if more than one independent variable or hypothesized mediator is specified, or if control variables are supplied. |
| robust | a logical indicating whether to robustly estimate the effects (defaults to TRUE). For estimation via regressions (method = "regression"), this can also be a character string, with "MM" specifying the MM-estimator of regression, and "median" specifying median regression. |
| family | a character string specifying the error distribution to be used in maximum likelihood estimation of regression models. Possible values are "gaussian" for a normal distribution (the default), skewnormal for a skew-normal distribution, "student" for Student's t distribution, "skewt" for a skew-t distribution, or "select" to select among these four distributions via BIC (see 'Details'). This is only relevant if method = "regression" and robust = FALSE. |
| model | a character string specifying the type of model in case of multiple mediators. Possible values are "parallel" (the default) for the parallel multiple mediator model, or "serial" for the serial multiple mediator model. This is only relevant for models with multiple hypothesized mediators, which are currently only implemented for estimation via regressions (method = "regression"). |
| contrast | a logical indicating whether to compute pairwise contrasts of the indirect effects (defaults to FALSE). This can also be a character string, with "estimates" for computing the pairwise differences of the indirect effects, and "absolute" for computing the pairwise differences of the absolute values of the indirect effects. This is only relevant for models with multiple indirect effects, which are currently only implemented for estimation via regressions (method = "regression"). For models with multiple independent variables of interest and multiple hypothesized mediators, contrasts are only computed between indirect effects corresponding to the same independent variable. |
| fit_yx | a logical indicating whether to fit the regression model $y \sim x + \text{covariates}$ to estimate the total effect (the default is TRUE). This is only relevant if method = "regression" and robust = FALSE. |
| control | a list of tuning parameters for the corresponding robust method. For robust regression (method = "regression", and robust = TRUE or robust = "MM"), a list of tuning parameters for <code>lmrob()</code> as generated by <code>reg_control()</code> . For win-sorized covariance matrix estimation (method = "covariance" and robust = |

TRUE), a list of tuning parameters for `cov_Huber()` as generated by `cov_control()`. No tuning parameters are necessary for median regression (`method = "regression"` and `robust = "median"`).

Details

With `method = "regression"`, and `robust = TRUE` or `robust = "MM"`, the effects are computed via the robust MM-estimator of regression from `lmrob()`. This is the default behavior.

With `method = "regression"` and `robust = "median"`, the effects are estimated via median regressions with `rq()`. Unlike the robust MM-regressions above, median regressions are not robust against outliers in the explanatory variables.

With `method = "regression"`, `robust = FALSE` and `family = "select"`, the error distribution to be used in maximum likelihood estimation of the regression models is selected via BIC. The following error distributions are included in the selection procedure: a normal distribution, a skew-normal distribution, Student's t distribution, and a skew-t distribution. Note that the parameters of those distributions are estimated as well. The skew-normal and skew-t distributions thereby use a centered parametrization such that the residuals are (approximately) centered around 0. Moreover, the skew-t distribution is only evaluated in the selection procedure if both the skew-normal and Student's t distribution yield an improvement in BIC over the normal distribution. Otherwise the estimation with a skew-t error distribution can be unstable. Furthermore, this saves a considerable amount of computation time in a bootstrap test, as estimation with those error distributions is orders of magnitude slower than any other estimation procedure in package **robmed**.

With `method = "covariance"` and `robust = TRUE`, the effects are estimated based on a Huber M-estimator of location and scatter. Note that this covariance-based approach is less robust than the approach based on robust MM-regressions described above.

Value

An object inheriting from class `"fit_mediation"` (class `"reg_fit_mediation"` if `method = "regression"` or `"cov_fit_mediation"` if `method = "covariance"`) with the following components:

| | |
|----------|---|
| a | a numeric vector containing the point estimates of the effects of the independent variables on the proposed mediator variables. |
| b | a numeric vector containing the point estimates of the direct effects of the proposed mediator variables on the dependent variable. |
| d | in case of a serial multiple mediator model, a numeric vector containing the point estimates of the effects of proposed mediator variables on other mediator variables occurring later in the sequence (only <code>"reg_fit_mediation"</code> if applicable). |
| total | a numeric vector containing the point estimates of the total effects of the independent variables on the dependent variable. |
| direct | a numeric vector containing the point estimates of the direct effects of the independent variables on the dependent variable. |
| indirect | a numeric vector containing the point estimates of the indirect effects. |
| ab | for back-compatibility with versions <0.10.0, the point estimates of the indirect effects are also included here. This component is deprecated and may be removed as soon as the next version. |

| | |
|---------------------|---|
| fit_mx | an object of class "lmrob", "rq", "lm" or "lmse" containing the estimation results from the regression of the proposed mediator variable on the independent variables, or a list of such objects in case of more than one hypothesized mediator (only "reg_fit_mediation"). |
| fit_ymx | an object of class "lmrob", "rq", "lm" or "lmse" containing the estimation results from the regression of the dependent variable on the proposed mediator and independent variables (only "reg_fit_mediation"). |
| fit_yx | an object of class "lm" or "lmse" containing the estimation results from the regression of the dependent variable on the independent variables (only "reg_fit_mediation" if arguments robust = FALSE and fit_yx = TRUE were used). |
| cov | an object of class "cov_Huber" or "cov_ML" containing the covariance matrix estimates (only "cov_fit_mediation"). |
| x, y, m, covariates | character vectors specifying the respective variables used. |
| data | a data frame containing the independent, dependent and proposed mediator variables, as well as covariates. |
| robust | either a logical indicating whether the effects were estimated robustly, or one of the character strings "MM" and "median" specifying the type of robust regressions. |
| model | a character string specifying the type of mediation model fitted: "simple" in case of one independent variable and one hypothesized mediator, "multiple" in case of multiple independent variables and one hypothesized mediator, "parallel" in case of parallel multiple mediators, or "serial" in case of serial multiple mediators (only "reg_fit_mediation"). |
| contrast | either a logical indicating whether contrasts of the indirect effects were computed, or one of the character strings "estimates" and "absolute" specifying the type of contrasts of the indirect effects (only "reg_fit_mediation"). |
| control | a list of tuning parameters used (if applicable). |

Note

The formula interface is still experimental and may change in future versions.

Author(s)

Andreas Alfons

References

- Alfons, A., Ates, N.Y. and Groenen, P.J.F. (2021) A robust bootstrap test for mediation analysis. *Organizational Research Methods*, doi: 10.1177/1094428121999096.
- Azzalini, A. and Arellano-Valle, R. B. (2013) Maximum penalized likelihood estimation for skew-normal and skew-t distributions. *Journal of Statistical Planning and Inference*, **143**(2), 419–433.
- Yuan, Y. and MacKinnon, D.P. (2014) Robust mediation analysis based on median regression. *Psychological Methods*, **19**(1), 1–20.
- Zu, J. and Yuan, K.-H. (2010) Local influence and robust procedures for mediation analysis. *Multivariate Behavioral Research*, **45**(1), 1–44.

See Also

`test_mediation()`
`lmrob()`, `lm()`, `cov_Huber()`, `cov_ML()`

Examples

```
data("BSG2014")

# set seed of the random number generator
set.seed(20211117)

## The results in Alfons et al. (2021) were obtained with an
## older version of the random number generator. To reproduce
## those results, uncomment the two lines below.
# RNGversion("3.5.3")
# set.seed(20150601)

# perform mediation analysis
fit <- fit_mediation(TeamCommitment ~ m(TaskConflict) + ValueDiversity,
                    data = BSG2014)
test <- test_mediation(fit)
summary(test)
```

m

Create an object of hypothesized mediators or control variables

Description

`m()` and its wrappers `parallel_m()` and `serial_m()` create an object of hypothesized mediators, while `covariates()` creates an object of control variables. Usually, these are used in a formula specifying a mediation model.

Usage

```
m(..., .model = c("parallel", "serial"))

parallel_m(...)

serial_m(...)

covariates(...)
```

Arguments

`...` variables are supplied as arguments, as usual separated by a comma.
`.model` a character string specifying the type of model in case of multiple mediators. Possible values are "parallel" (the default) for the parallel multiple mediator model, or "serial" for the serial multiple mediator model.

Details

`m()` and `covariates()` are essentially wrappers for `cbind()` with a specific class prepended to the class(es) of the resulting object.

`parallel_m()` and `serial_m()` are wrappers for `m()` with the respective value for argument `.model`.

Value

`m()` returns an object inheriting from class "mediators" (with subclass "parallel_mediators" or "serial_mediators" as specified by argument `.model`), and `covariates()` returns an object of class "covariates". Typically, these inherit from class "matrix".

Note

The formula interface is still experimental and may change in future versions.

Author(s)

Andreas Alfons

See Also

`fit_mediation()`, `test_mediation()`

Examples

```
data("BSG2014")

# inside formula
fit_mediation(TeamCommitment ~ m(TaskConflict) + ValueDiversity,
              data = BSG2014)

# outside formula
mediator <- with(BSG2014, m(TaskConflict))
fit_mediation(TeamCommitment ~ mediator + ValueDiversity,
              data = BSG2014)
```

Description

Visualize results from (robust) mediation analysis.

Usage

```
## S3 method for class 'fit_mediation'  
autoplot(object, which = c("ellipse", "weight"), ...)  
  
## S3 method for class 'test_mediation'  
autoplot(object, which = c("ci", "density", "ellipse", "weight"), ...)  
  
## S3 method for class 'fit_mediation'  
plot(x, which = c("ellipse", "weight"), ...)  
  
## S3 method for class 'test_mediation'  
plot(x, which = c("ci", "density", "ellipse", "weight"), ...)
```

Arguments

| | |
|-----------|--|
| object, x | an object inheriting from class " fit_mediation " or " test_mediation " containing results from (robust) mediation analysis. |
| which | a character string specifying which plot to produce. Possible values are "ci" for a dot plot of selected effects together with confidence intervals (see ci_plot()), "density" for a density plot of the indirect effect(s) (see density_plot()), "ellipse" for a diagnostic plot of the data together with a tolerance ellipse (see ellipse_plot()), and "weight" for a diagnostic plot of robust regression weights (see weight_plot()). |
| ... | additional arguments to be passed down. |

Details

The "[fit_mediation](#)" method calls [ellipse_plot\(\)](#) or [weight_plot\(\)](#), depending on the argument which.

The "[test_mediation](#)" method calls [ci_plot\(\)](#), [density_plot\(\)](#), [ellipse_plot\(\)](#), or [weight_plot\(\)](#), depending on the argument which.

Value

An object of class "[ggplot](#)".

Author(s)

Andreas Alfons

See Also

[fit_mediation\(\)](#), [test_mediation\(\)](#)
[ci_plot\(\)](#), [density_plot\(\)](#), [ellipse_plot\(\)](#), [weight_plot\(\)](#)

Examples

```
data("BSG2014")

# run fast-and-robust bootstrap test
test <- test_mediation(BSG2014,
  x = "ValueDiversity",
  y = "TeamCommitment",
  m = "TaskConflict")

# create plots for robust bootstrap test
plot(test, which = "ci")
plot(test, which = "density")
plot(test, which = "ellipse")
plot(test, which = "weight")
```

p_value

p-Values from (robust) mediation analysis

Description

Compute or extract the p-values for effects in (robust) mediation analysis.

Usage

```
p_value(object, ...)

## S3 method for class 'boot_test_mediation'
p_value(object, parm = NULL, type = c("boot", "data"), digits = 4L, ...)

## S3 method for class 'sobel_test_mediation'
p_value(object, parm = NULL, ...)
```

Arguments

| | |
|--------|--|
| object | an object inheriting from class " <code>test_mediation</code> " containing results from (robust) mediation analysis. |
| ... | for the generic function, additional arguments to be passed down to methods. For the methods, additional arguments are currently ignored. |
| parm | an integer, character or logical vector specifying the paths for which to extract or compute p-values, or NULL to extract or compute p-values for all coefficients. In case of a character vector, possible values are "a", "b", "d" (only serial multiple mediator models), "total", "direct", and "indirect". |
| type | a character string specifying how to compute the p-values of the effects other than the indirect effect(s). Possible values are "boot" (the default) to compute bootstrap p-values using the normal approximation (i.e., to assume a normal distribution of the corresponding effect with the standard deviation computed from |

the bootstrap replicates), or "data" to compute p-values via statistical theory based on the original data (e.g., based on a t-distribution if the coefficients are estimated via regression). Note that this is only relevant for mediation analysis via a bootstrap test, where the p-value of the indirect effect is always computed as described in 'Details'.

digits an integer determining how many digits to compute for the p-values of the indirect effects (see 'Details'). The default is to compute 4 digits after the comma.

Details

For bootstrap tests, the p-value of the indirect effect is computed as the smallest significance level α for which the $(1 - \alpha) * 100\%$ confidence interval obtained from the bootstrapped distribution does not contain 0.

This is a simple implementation, where each digit after the comma is determined via a grid search. Hence computation time can be long if confidence intervals are computed via the bias-corrected and accelerated method ("bca").

For Sobel tests, the p-value of the indirect effect is already stored in the object returned by `test_mediation()` and is simply extracted.

Value

A numeric vector containing the requested p-values.

Author(s)

Andreas Alfons

See Also

`test_mediation()`, `coef()`, `confint()`

Examples

```
data("BSG2014")

# BCa intervals are recommended, but take a while to run
test_bca <- test_mediation(BSG2014,
  x = "ValueDiversity",
  y = "TeamCommitment",
  m = "TaskConflict",
  type = "bca")

p_value(test_bca)
```

`reg_control`*Tuning parameters for MM-regression*

Description

Obtain a list with tuning parameters for `lmrob()`.

Usage

```
reg_control(efficiency = 0.85, max_iterations = 200, tol = 1e-07, seed = NULL)
```

Arguments

| | |
|-----------------------------|---|
| <code>efficiency</code> | a numeric value giving the desired efficiency (defaults to 0.85 for 85% efficiency). |
| <code>max_iterations</code> | an integer giving the maximum number of iterations in various parts of the algorithm. |
| <code>tol</code> | a small positive numeric value to be used to determine convergence in various parts of the algorithm. |
| <code>seed</code> | optional initial seed for the random number generator (see <code>.Random.seed</code>). |

Value

A list of tuning parameters as returned by `lmrob.control()`.

Note

This is a simplified wrapper function for `lmrob.control()`, as the latter requires detailed knowledge of the MM-type regression algorithm. Currently only 95%, 90%, 85% (the default) and 80% efficiency are supported. For other values, please specify the corresponding tuning parameters in `lmrob.control()` directly.

Author(s)

Andreas Alfons

References

Salibian-Barrera, M. and Yohai, V.J. (1987) A fast algorithm for S-regression estimates. *Journal of Computational and Graphical Statistics*, **15**(2), 414–427.

Yohai, V.J. (1987) High breakdown-point and high efficiency estimates for regression. *The Annals of Statistics*, **15**(20), 642–656.

See Also

`lmrob()`, `lmrob.control()`

Examples

```
data("BSG2014")

# run fast-and-robust bootstrap test
ctrl <- reg_control(efficiency = 0.95)
test <- test_mediation(BSG2014,
  x = "ValueDiversity",
  y = "TeamCommitment",
  m = "TaskConflict",
  control = ctrl)

summary(test)
```

retest

Retest for mediation

Description

Re-perform a test for the indirect effect(s) based on results from (robust) mediation analysis. This function is purely available for computational convenience if the analysis was accidentally run with the wrong parameter settings, as it avoids having to re-run the bootstrap procedure. It must not be abused for p -hacking.

Usage

```
retest(object, ...)

## S3 method for class 'boot_test_mediation'
retest(object, alternative, level, type, contrast, ...)

## S3 method for class 'sobel_test_mediation'
retest(object, alternative, order, ...)
```

Arguments

| | |
|-------------|---|
| object | an object inheriting from class " <code>test_mediation</code> " containing results from (robust) mediation analysis. |
| ... | additional arguments to be passed down to methods. |
| alternative | a character string specifying the alternative hypothesis in the test for the indirect effect. Possible values are "twosided", "less" or "greater". |
| level | numeric; the confidence level of the confidence interval in the bootstrap test. |
| type | a character string specifying the type of confidence interval to be computed in the bootstrap test. Possible values are "bca" for the bias-corrected and accelerated bootstrap, or "perc" for the percentile bootstrap. |

| | |
|----------|--|
| contrast | a logical indicating whether to compute pairwise contrasts of the indirect effects. This can also be a character string, with "estimates" for computing the pairwise differences of the indirect effects (such that it is tested whether two indirect effects are equal), and "absolute" for computing the pairwise differences of the absolute values of the indirect effects (such that it is tested whether two indirect effects are equal in magnitude). This is only relevant for models with multiple indirect effects, which are currently only implemented for bootstrap tests and estimation via regressions. |
| order | a character string specifying the order of approximation of the standard error in Sobel's test. Possible values are "first" for a first-order approximation, and "second" for a second-order approximation. |

Value

An object of the same class as object with updated test results (see [test_mediation\(\)](#)).

Note

From version 0.9.0 onwards, the behavior of this function changed. For arguments that are not supplied, the corresponding values of object are now used as defaults.

Author(s)

Andreas Alfons

See Also

[test_mediation\(\)](#)

Examples

```
data("BSG2014")

# run fast-and-robust bootstrap test
test <- test_mediation(BSG2014,
  x = "ValueDiversity",
  y = "TeamCommitment",
  m = "TaskConflict")

summary(test)

# now compute 97.5% confidence interval
retest(test, level = 0.975)
```

| | |
|---------------|--|
| setup_ci_plot | <i>Set up information for a dot plot with confidence intervals</i> |
|---------------|--|

Description

Extract the relevant information for a dot plot with confidence intervals of selected effects from (robust) mediation analysis. Information on p-values of the selected effects can be included in addition to confidence intervals.

Usage

```
setup_ci_plot(object, ...)

## S3 method for class 'boot_test_mediation'
setup_ci_plot(
  object,
  parm = c("direct", "indirect"),
  type = c("boot", "data"),
  p_value = FALSE,
  digits = 4L,
  ...
)

## S3 method for class 'sobel_test_mediation'
setup_ci_plot(
  object,
  parm = c("direct", "indirect"),
  level = 0.95,
  p_value = FALSE,
  ...
)

## S3 method for class 'list'
setup_ci_plot(object, ...)
```

Arguments

| | |
|--------|---|
| object | an object inheriting from class " <code>test_mediation</code> " containing results from (robust) mediation analysis, or a list of such objects. |
| ... | additional arguments to be passed down. |
| parm | an integer, character or logical vector specifying which effects to include in the plot. In case of a character vector, possible values are "a", "b", "d" (only serial multiple mediator models), "total", "direct", and "indirect". The default is to include the direct and the indirect effect(s). |
| type | a character string specifying which point estimates and confidence intervals to plot: those based on the bootstrap distribution ("boot"; the default), or those |

based on the original data ("data"). If "boot", the confidence intervals of effects other than the indirect effect(s) are computed using a normal approximation (i.e., assuming a normal distribution of the corresponding effect with the standard deviation computed from the bootstrap replicates). If "data", the confidence intervals of effects other than the indirect effect(s) are computed via statistical theory based on the original data (e.g., based on a t-distribution if the coefficients are estimated via regression). Note that this is only relevant for mediation analysis via a bootstrap test, where the confidence interval of the indirect effect is always computed via a percentile-based method due to the asymmetry of its distribution.

| | |
|---------|--|
| p_value | a logical indicating whether to include information on the p-values in addition to the confidence intervals. The default is FALSE. |
| digits | an integer determining how many digits to compute for bootstrap p-values of the indirect effects (see <code>p_value()</code>). The default is to compute 4 digits after the comma. This is only relevant if <code>p_value = TRUE</code> . |
| level | numeric; the confidence level of the confidence intervals from Sobel's test. The default is to include 95% confidence intervals. Note that this is not used for bootstrap tests, as those require to specify the confidence level already in <code>test_mediation()</code> . |

Details

This function is used internally by `ci_plot()`. It may also be useful for users who want to produce a similar plot, but who want more control over what information to display or how to display that information.

Value

An object of class "setup_ci_plot" with the following components:

| | |
|--------------|--|
| ci | a data frame consisting of column <code>Effect</code> indicating the different effects, column <code>Estimate</code> containing the point estimates, column <code>Lower</code> for the lower confidence limit, and column <code>Upper</code> for the upper confidence limit. If argument <code>p_value = TRUE</code> , there is an additional column <code>Label</code> which gives the default facet label for the confidence intervals. If a list of "test_mediation" objects has been supplied, there is also a column <code>Method</code> , which takes the names or indices of the list elements to indicate the different methods. |
| p_value | a data frame consisting of column <code>Label</code> which gives the default facet label for the p-values, column <code>Effect</code> indicating the different effects, and column <code>Value</code> containing the p-values. If a list of "test_mediation" objects has been supplied, there is also a column <code>Method</code> , which takes the names or indices of the list elements to indicate the different methods. This is only returned if argument <code>p_value = TRUE</code> . |
| level | numeric; the confidence level used for the confidence intervals of the indirect effect(s). |
| have_methods | a logical indicating whether a list of "test_mediation" objects has been supplied. If TRUE, the data frame in the <code>ci</code> component contains a column <code>Method</code> . |

Author(s)

Andreas Alfons

See Also`test_mediation()`, `ci_plot()`**Examples**

```

data("BSG2014")

# run fast-and-robust bootstrap test
test <- test_mediation(BSG2014,
  x = "ValueDiversity",
  y = "TeamCommitment",
  m = "TaskConflict")

# set up information for plot
setup <- setup_ci_plot(test, parm = "Indirect")

# plot only density and confidence interval
ggplot() +
  geom_hline(yintercept = 0, color = "darkgrey") +
  geom_pointrange(aes(x = "Robust bootstrap", y = Estimate,
    ymin = Lower, ymax = Upper),
    data = setup$ci) +
  labs(x = NULL, y = "Indirect effect")

```

`setup_density_plot` *Set up information for a density plot of the indirect effect(s)*

Description

Extract the relevant information for a density plot of the indirect effect(s) from results of (robust) mediation analysis.

Usage

```

setup_density_plot(object, ...)

## S3 method for class 'boot_test_mediation'
setup_density_plot(object, ...)

## S3 method for class 'sobel_test_mediation'
setup_density_plot(object, grid = NULL, level = 0.95, ...)

## S3 method for class 'list'
setup_density_plot(object, ...)

```

Arguments

| | |
|--------|---|
| object | an object inheriting from class " <code>test_mediation</code> " containing results from (robust) mediation analysis, or a list of such objects. |
| ... | additional arguments to be passed down. |
| grid | an optional numeric vector containing the values at which to evaluate the assumed normal density from Sobel's test. The default is to take 512 equally spaced points between the estimated indirect effect \pm three times the standard error according to Sobel's formula. |
| level | numeric; the confidence level of the confidence intervals from Sobel's test. The default is to include 95% confidence intervals. Note that this is not used for bootstrap tests, as those require to specify the confidence level already in <code>test_mediation()</code> . |

Details

This function is used internally by `density_plot()`. It may also be useful for users who want to produce a similar plot, but who want more control over what information to display or how to display that information.

Value

An object of class "`setup_density_plot`" with the following components:

| | |
|--------------|---|
| density | a data frame containing the values of the indirect effect where the density is estimated (column <code>Indirect</code>), and the estimated density values (column <code>Density</code>). In case of a model with multiple indirect effects, there is a column <code>Effect</code> that indicates the different indirect effects. If a list of " <code>test_mediation</code> " objects has been supplied, there is also a column <code>Method</code> , which takes the names or indices of the list elements to indicate the different methods. |
| ci | a data frame consisting of column <code>Estimate</code> containing the point estimates, column <code>Lower</code> for the lower confidence limit, and column <code>Upper</code> for the upper confidence limit. In case of a model with multiple indirect effects, there is a column <code>Effect</code> that indicates the different indirect effects. If a list of " <code>test_mediation</code> " objects has been supplied, there is also a column <code>Method</code> , which takes the names or indices of the list elements to indicate the different methods. |
| test | a character string indicating whether the object contains results from a bootstrap test (" <code>boot</code> ") or a Sobel test (" <code>sobel</code> "), or a vector of such character strings if a list of " <code>test_mediation</code> " objects has been supplied. |
| level | numeric; the confidence level used for the confidence intervals of the indirect effect(s). |
| have_effects | a logical indicating whether the mediation model contains multiple indirect effects. If <code>TRUE</code> , the data frames in the <code>density</code> and <code>ci</code> components contain a column <code>Effect</code> . |
| have_methods | a logical indicating whether a list of " <code>test_mediation</code> " objects has been supplied. If <code>TRUE</code> , the data frames in the <code>density</code> and <code>ci</code> components contain a column <code>Method</code> . |

Author(s)

Andreas Alfons

See Also`test_mediation()`, `density_plot()`**Examples**

```
data("BSG2014")

# run fast-and-robust bootstrap test
test <- test_mediation(BSG2014,
  x = "ValueDiversity",
  y = "TeamCommitment",
  m = "TaskConflict")

# set up information for plot
setup <- setup_density_plot(test)

# plot only density and confidence interval
ggplot() +
  geom_density(aes(x = Indirect, y = Density), data = setup$density,
    stat = "identity") +
  geom_rect(aes(xmin = Lower, xmax = Upper,
    ymin = -Inf, ymax = Inf),
    data = setup$ci, color = NA, alpha = 0.2) +
  labs(x = "Indirect effect", y = "Bootstrap density")
```

setup_ellipse_plot *Set up a diagnostic plot with a tolerance ellipse*

Description

Extract the relevant information for a diagnostic plot with a tolerance ellipse from results of (robust) mediation analysis.

Usage

```
setup_ellipse_plot(object, ...)
```

S3 method for class 'test_mediation'

```
setup_ellipse_plot(object, ...)
```

S3 method for class 'reg_fit_mediation'

```
setup_ellipse_plot(
  object,
```

```

    horizontal = NULL,
    vertical = NULL,
    partial = FALSE,
    level = 0.975,
    npoints = 100,
    ...
)

## S3 method for class 'cov_fit_mediation'
setup_ellipse_plot(
  object,
  horizontal = NULL,
  vertical = NULL,
  partial = FALSE,
  level = 0.975,
  npoints = 100,
  ...
)

## S3 method for class 'list'
setup_ellipse_plot(object, ...)

```

Arguments

| | |
|-------------------------|---|
| <code>object</code> | an object inheriting from class <code>"fit_mediation"</code> or <code>"test_mediation"</code> containing results from (robust) mediation analysis, or a list of such objects. |
| <code>...</code> | additional arguments to be passed down. |
| <code>horizontal</code> | a character string specifying the variable to be plotted on the horizontal axis. If the dependent variable is chosen for the vertical axis, a hypothesized mediator or an independent variable must be selected for the horizontal axis. If a hypothesized mediator is chosen for the vertical axis, an independent variable must be selected for the horizontal axis (in case of a serial multiple mediator model, a hypothesized mediator occurring earlier in the sequence is also allowed). The default is to plot the first independent variable on the horizontal axis. |
| <code>vertical</code> | a character string specifying the variable to be plotted on the vertical axis: the dependent variable or a hypothesized mediator. The default is to plot the first hypothesized mediator on the vertical axis. |
| <code>partial</code> | a logical indicating whether to extract the observed values of the selected variable for the vertical axis (FALSE), or the partial residuals with respect to the variable on the horizontal axis (TRUE). The latter allows to display the corresponding regression coefficient by a line. |
| <code>level</code> | numeric; the confidence level of the tolerance ellipse. It gives the percentage of observations that are expected to lie within the ellipse under the assumption of a normal distribution, and therefore it controls the size of the ellipse. The default is such that the ellipse is expected to contain 97.5% of the observations. |
| <code>npoints</code> | the number of grid points used to evaluate the ellipse. The default is to use 100 grid points. |

Details

This function is used internally by `ellipse_plot()`. It may also be useful for users who want to produce a similar plot, but who want more control over what information to display or how to display that information.

Value

An object of class "setup_ellipse_plot" with the following components:

| | |
|---------------------------|---|
| <code>data</code> | a data frame containing the coordinates of the data points to be plotted on the horizontal axis (column <code>x</code>) and the coordinates on the vertical axis (column <code>y</code>). For robust methods that assign outlyingness weights to each data point, those weights are given in column <code>Weight</code> . If a list of objects has been supplied and there are multiple objects from such robust methods, or if partial residuals are to be plotted on the vertical axis, there is also a column <code>Method</code> , which takes the names or indices of the list elements to indicate the different methods. |
| <code>ellipse</code> | a data frame containing the coordinates of the tolerance ellipse on the horizontal axis (column <code>x</code>) and on the vertical axis (column <code>y</code>). If a list of objects has been supplied, there is also a column <code>Method</code> , which takes the names or indices of the list elements to indicate the different methods. |
| <code>line</code> | a data frame with columns <code>intercept</code> and <code>slope</code> containing the intercept and slope, respectively, of the regression line to be plotted. If a list of objects has been supplied, there is also a column <code>Method</code> , which takes the names or indices of the list elements to indicate the different methods. This is only returned if <code>partial = TRUE</code> , or in case of a simple mediation model (without control variables) when the hypothesized mediator is plotted on the vertical axis and the independent variable is plotted on the horizontal axis. |
| <code>horizontal</code> | a character string giving the variable to be plotted on the horizontal axis. |
| <code>vertical</code> | a character string giving the variable to be plotted on the vertical axis |
| <code>partial</code> | a logical indicating whether the values to be plotted on the vertical axis correspond to the observed values of the selected variable (<code>FALSE</code>), or the partial residuals with respect to the variable on the horizontal axis (<code>TRUE</code>). |
| <code>robust</code> | a logical indicating whether the object contains results from a robust method, or a vector of such logicals if a list of objects has been supplied. |
| <code>have_methods</code> | a logical indicating whether a list of objects has been supplied. |

Author(s)

Andreas Alfons

See Also

`fit_mediation()`, `test_mediation()`, `ellipse_plot()`

Examples

```

data("BSG2014")

# run fast-and-robust bootstrap test
test <- test_mediation(BSG2014,
  x = "ValueDiversity",
  y = "TeamCommitment",
  m = "TaskConflict")

# set up information for plot
setup <- setup_ellipse_plot(test)

# plot only data and tolerance ellipse
ggplot() +
  geom_path(aes(x = x, y = y), data = setup$ellipse,
    color = "#00BFC4") +
  geom_point(aes(x = x, y = y, fill = Weight),
    data = setup$data, shape = 21) +
  scale_fill_gradient(limits = 0:1, low = "white",
    high = "black") +
  labs(x = setup$horizontal, y = setup$vertical)

```

| | |
|-------------------|--|
| setup_weight_plot | <i>Set up a diagnostic plot of robust regression weights</i> |
|-------------------|--|

Description

Extract the relevant information for a diagnostic plot of the regression weights from robust mediation analysis. This plot allows to easily detect deviations from normality assumptions such as skewness or heavy tails.

Usage

```

setup_weight_plot(object, ...)

## S3 method for class 'test_mediation'
setup_weight_plot(object, ...)

## S3 method for class 'reg_fit_mediation'
setup_weight_plot(object, outcome = NULL, npoints = 1000, ...)

```

Arguments

| | |
|--------|---|
| object | an object inheriting from class <code>"fit_mediation"</code> or <code>"test_mediation"</code> containing results from robust mediation analysis. Only mediation analysis objects fitted with the robust MM-estimator are supported. |
| ... | additional arguments to be passed down. |

| | |
|---------|---|
| outcome | a character vector specifying the outcome variables of the regressions to be included in the plot. This must be a subset of the hypothesized mediators and the dependent variable, or NULL (the default) to include all regressions of the mediation model. |
| npoints | the number of grid points used to evaluate the expected percentages. The default is to use 1000 grid points. |

Details

This function is used internally by `weight_plot()`. It may also be useful for users who want to produce a similar plot, but who want more control over what information to display or how to display that information.

Value

An object of class "setup_weight_plot" with the following components:

| | |
|---------|--|
| data | a data frame containing the following information: the outcome variable of the regression (column Outcome; only if multiple regressions are to be included in the plot), whether the row corresponds to the negative or the positive tail of the residual distribution (column Tail), whether the row corresponds to the expected (under the normal distribution) or the empirical weights (column Weights), the weight thresholds (column Threshold), and the corresponding percentage of observations that have a weight below this threshold (column Percentage). |
| outcome | a character vector containing the outcome variables of the regressions to be included in the plot. |

Author(s)

Andreas Alfons

See Also

`fit_mediation()`, `test_mediation()`, `weight_plot()`

Examples

```
data("BSG2014")

# run fast-and-robust bootstrap test
test <- test_mediation(BSG2014,
  x = "ValueDiversity",
  y = "TeamCommitment",
  m = "TaskConflict")

# set up information for plot
setup <- setup_weight_plot(test)
# create diagnostic plot of robust regression weights
weight_plot(setup) +
  scale_color_manual("", values = c("black", "#00BFC4")) +
```

```
theme(legend.position = "top")
```

```
summary.test_mediation
```

Summary of results from (robust) mediation analysis

Description

Summarize results from (robust) mediation analysis for proper interpretation.

Usage

```
## S3 method for class 'boot_test_mediation'
summary(object, type = c("boot", "data"), plot = TRUE, ...)

## S3 method for class 'sobel_test_mediation'
summary(object, ...)
```

Arguments

| | |
|--------|--|
| object | an object inheriting from class " test_mediation " containing results from (robust) mediation analysis. |
| type | a character string specifying how to summarize the effects other than the indirect effect(s). Possible values are "boot" (the default) to compute significance tests using the normal approximation of the bootstrap distribution (i.e., to assume a normal distribution of the corresponding effect with the standard deviation computed from the bootstrap replicates), or "data" to compute significance tests via statistical theory based on the original data (e.g., t-tests if the coefficients are estimated via regression). Note that this is only relevant for mediation analysis via a bootstrap test, where significance of the indirect effect is always assessed via a percentile-based confidence interval due to the asymmetry of its distribution. |
| plot | a logical indicating whether to produce a diagnostic plot of robust regression weights (see weight_plot()). This is only used for mediation analysis objects fitted with the robust MM-estimator (see test_mediation()). |
| ... | additional arguments are currently ignored. |

Value

An object of class "[summary_test_mediation](#)" with the following components:

| | |
|---------|--|
| object | the object passed to the summary method, which contains the results from testing the indirect effect(s). |
| summary | an object containing all necessary information to summarize the effects other than the indirect effect(s). |

Author(s)

Andreas Alfons

References

Alfons, A., Ates, N.Y. and Groenen, P.J.F. (2021) A robust bootstrap test for mediation analysis. *Organizational Research Methods*, doi: 10.1177/1094428121999096.

See Also[test_mediation](#)**Examples**

```
data("BSG2014")

# set seed of the random number generator
set.seed(20211117)

## The results in Alfons et al. (2021) were obtained with an
## older version of the random number generator. To reproduce
## those results, uncomment the two lines below.
# RNGversion("3.5.3")
# set.seed(20150601)

# perform mediation analysis
test <- test_mediation(TeamCommitment ~ m(TaskConflict) + ValueDiversity,
                      data = BSG2014)
summary(test)
```

| | |
|----------------|------------------------------------|
| test_mediation | <i>(Robust) mediation analysis</i> |
|----------------|------------------------------------|

Description

Perform (robust) mediation analysis via a (fast-and-robust) bootstrap test or Sobel's test.

Usage

```
test_mediation(object, ...)

## S3 method for class 'formula'
test_mediation(
  formula,
  data,
  test = c("boot", "sobel"),
  alternative = c("twosided", "less", "greater"),
```

```

R = 5000,
level = 0.95,
type = c("bca", "perc"),
order = c("first", "second"),
method = c("regression", "covariance"),
robust = TRUE,
family = "gaussian",
contrast = FALSE,
fit_yx = TRUE,
control = NULL,
...
)

## Default S3 method:
test_mediation(
  object,
  x,
  y,
  m,
  covariates = NULL,
  test = c("boot", "sobel"),
  alternative = c("twosided", "less", "greater"),
  R = 5000,
  level = 0.95,
  type = c("bca", "perc"),
  order = c("first", "second"),
  method = c("regression", "covariance"),
  robust = TRUE,
  family = "gaussian",
  model = c("parallel", "serial"),
  contrast = FALSE,
  fit_yx = TRUE,
  control = NULL,
  ...
)

## S3 method for class 'fit_mediation'
test_mediation(
  object,
  test = c("boot", "sobel"),
  alternative = c("twosided", "less", "greater"),
  R = 5000,
  level = 0.95,
  type = c("bca", "perc"),
  order = c("first", "second"),
  ...
)

```

```
robmed(..., test = "boot", method = "regression", robust = TRUE)
```

Arguments

| | |
|-------------|--|
| object | the first argument will determine the method of the generic function to be dispatched. For the default method, this should be a data frame containing the variables. There is also a method for a mediation model fit as returned by <code>fit_mediation()</code> . |
| ... | additional arguments to be passed down. For the bootstrap tests, those can be used to specify arguments of <code>boot()</code> , for example for parallel computing. |
| formula | an object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted. Hypothesized mediator variables should be wrapped in a call to <code>m()</code> (see examples), and any optional control variables should be wrapped in a call to <code>covariates()</code> . |
| data | for the formula method, a data frame containing the variables. |
| test | a character string specifying the test to be performed for the indirect effects. Possible values are "boot" (the default) for the bootstrap, or "sobel" for Sobel's test. Currently, Sobel's test is not implemented for models with multiple indirect effects. |
| alternative | a character string specifying the alternative hypothesis in the test for the indirect effects. Possible values are "twosided" (the default), "less" or "greater". |
| R | an integer giving the number of bootstrap replicates. The default is to use 5000 bootstrap replicates. |
| level | numeric; the confidence level of the confidence interval in the bootstrap test. The default is to compute a 95% confidence interval. |
| type | a character string specifying the type of confidence interval to be computed in the bootstrap test. Possible values are "bca" (the default) for the bias-corrected and accelerated bootstrap, or "perc" for the percentile bootstrap. |
| order | a character string specifying the order of approximation of the standard error in Sobel's test. Possible values are "first" (the default) for a first-order approximation, and "second" for a second-order approximation. |
| method | a character string specifying the method of estimation for the mediation model. Possible values are "regression" (the default) to estimate the effects via regressions, or "covariance" to estimate the effects via the covariance matrix. Note that the effects are always estimated via regressions if more than one independent variable or hypothesized mediator is specified, or if control variables are supplied. |
| robust | a logical indicating whether to perform a robust test (defaults to TRUE). For estimation via regressions (method = "regression"), this can also be a character string, with "MM" specifying the MM-estimator of regression, and "median" specifying median regression. |
| family | a character string specifying the error distribution to be used in maximum likelihood estimation of regression models. Possible values are "gaussian" for a normal distribution (the default), skewnormal for a skew-normal distribution, "student" for Student's t distribution, "skewt" for a skew-t distribution, or |

| | |
|-------------------------|--|
| | "select" to select among these four distributions via BIC (see <code>fit_mediation()</code> for details). This is only relevant if <code>method = "regression"</code> and <code>robust = FALSE</code> . |
| <code>contrast</code> | a logical indicating whether to compute pairwise contrasts of the indirect effects (defaults to <code>FALSE</code>). This can also be a character string, with <code>"estimates"</code> for computing the pairwise differences of the indirect effects (such that it is tested whether two indirect effects are equal), and <code>"absolute"</code> for computing the pairwise differences of the absolute values of the indirect effects (such that it is tested whether two indirect effects are equal in magnitude). This is only relevant for models with multiple indirect effects, which are currently only implemented for estimation via regressions (<code>method = "regression"</code>). For models with multiple independent variables of interest and multiple hypothesized mediators, contrasts are only computed between indirect effects corresponding to the same independent variable. |
| <code>fit_yx</code> | a logical indicating whether to fit the regression model $y \sim x + \text{covariates}$ to estimate the total effect (the default is <code>TRUE</code>). This is only relevant if <code>method = "regression"</code> and <code>robust = FALSE</code> . |
| <code>control</code> | a list of tuning parameters for the corresponding robust method. For robust regression (<code>method = "regression"</code> , and <code>robust = TRUE</code> or <code>robust = "MM"</code>), a list of tuning parameters for <code>lmrob()</code> as generated by <code>reg_control()</code> . For winzorized covariance matrix estimation (<code>method = "covariance"</code> and <code>robust = TRUE</code>), a list of tuning parameters for <code>cov_Huber()</code> as generated by <code>cov_control()</code> . No tuning parameters are necessary for median regression (<code>method = "regression"</code> and <code>robust = "median"</code>). |
| <code>x</code> | a character, integer or logical vector specifying the columns of object containing the independent variables of interest. |
| <code>y</code> | a character string, an integer or a logical vector specifying the column of object containing the dependent variable. |
| <code>m</code> | a character, integer or logical vector specifying the columns of object containing the hypothesized mediator variables. |
| <code>covariates</code> | optional; a character, integer or logical vector specifying the columns of object containing additional covariates to be used as control variables. |
| <code>model</code> | a character string specifying the type of model in case of multiple mediators. Possible values are <code>"parallel"</code> (the default) for the parallel multiple mediator model, or <code>"serial"</code> for the serial multiple mediator model. This is only relevant for models with multiple hypothesized mediators, which are currently only implemented for estimation via regressions (<code>method = "regression"</code>). |

Details

With `method = "regression"`, and `robust = TRUE` or `robust = "MM"`, the tests are based on robust regressions with the MM-estimator from `lmrob()`. The bootstrap test is thereby performed via the fast-and-robust bootstrap. This is the default behavior.

Note that the MM-estimator of regression implemented in `lmrob()` can be seen as weighted least squares estimator, where the weights are dependent on how much an observation is deviating from the rest. The trick for the fast-and-robust bootstrap is that on each bootstrap sample, first a weighted

least squares estimator is computed (using those robustness weights from the original sample) followed by a linear correction of the coefficients. The purpose of this correction is to account for the additional uncertainty of obtaining the robustness weights.

With `method = "regression"` and `robust = "median"`, the tests are based on median regressions with `rq()`. Note that the bootstrap test is performed via the standard bootstrap, as the fast-and-robust bootstrap is not applicable. Unlike the robust regressions described above, median regressions are not robust against outliers in the explanatory variables, and the standard bootstrap can suffer from oversampling of outliers in the bootstrap samples.

With `method = "covariance"` and `robust = TRUE`, the tests are based on a Huber M-estimator of location and scatter. For the bootstrap test, the M-estimates are used to first clean the data via a transformation. Then the standard bootstrap is performed with the cleaned data. Note that this covariance-based approach is less robust than the approach based on robust regressions described above. Furthermore, the bootstrap does not account for the variability from cleaning the data.

`robmed()` is a wrapper function for performing robust mediation analysis via regressions and the fast-and-robust bootstrap.

Value

An object inheriting from class `"test_mediation"` (class `"boot_test_mediation"` if `test = "boot"` or `"sobel_test_mediation"` if `test = "sobel"`) with the following components:

| | |
|-----------------------|---|
| <code>a</code> | a numeric vector containing the bootstrap point estimates of the effects of the independent variables on the proposed mediator variables (only <code>"boot_test_mediation"</code>). |
| <code>b</code> | a numeric vector containing the bootstrap point estimates of the direct effects of the proposed mediator variables on the dependent variable (only <code>"boot_test_mediation"</code>). |
| <code>d</code> | in case of a serial multiple mediator model, a numeric vector containing the bootstrap point estimates of the effects of proposed mediator variables on other mediator variables occurring later in the sequence (only <code>"boot_test_mediation"</code> if applicable). |
| <code>total</code> | a numeric vector containing the bootstrap point estimates of the total effects of the independent variables on the dependent variable (only <code>"boot_test_mediation"</code>). |
| <code>direct</code> | a numeric vector containing the bootstrap point estimates of the direct effects of the independent variables on the dependent variable (only <code>"boot_test_mediation"</code>). |
| <code>indirect</code> | a numeric vector containing the bootstrap point estimates of the indirect effects (only <code>"boot_test_mediation"</code>). |
| <code>ab</code> | for back-compatibility with versions <0.10.0, the bootstrap point estimates of the indirect effects are also included here (only <code>"boot_test_mediation"</code>). This component is deprecated and may be removed as soon as the next version. |
| <code>ci</code> | a numeric vector of length two or a matrix of two columns containing the bootstrap confidence intervals for the indirect effects (only <code>"boot_test_mediation"</code>). |
| <code>reps</code> | an object of class <code>"boot"</code> containing the bootstrap replicates (only <code>"boot_test_mediation"</code>). For regression model fits, bootstrap replicates of the coefficients in the individual regression models are stored. |
| <code>se</code> | numeric; the standard error of the indirect effect according to Sobel's formula (only <code>"sobel_test_mediation"</code>). |

| | |
|-------------|--|
| statistic | numeric; the test statistic for Sobel's test (only "sobel_test_mediation"). |
| p_value | numeric; the p-value from Sobel's test (only "sobel_test_mediation"). |
| alternative | a character string specifying the alternative hypothesis in the test for the indirect effects. |
| R | an integer giving the number of bootstrap replicates (only "boot_test_mediation"). |
| level | numeric; the confidence level of the bootstrap confidence interval (only "boot_test_mediation"). |
| type | a character string specifying the type of bootstrap confidence interval (only "boot_test_mediation"). |
| fit | an object inheriting from class "fit_mediation" containing the estimation results of the mediation model on the original data. |

Note

For the fast-and-robust bootstrap, the simpler correction of Salibian-Barrera & Van Aelst (2008) is used rather than the originally proposed correction of Salibian-Barrera & Zamar (2002).

The formula interface is still experimental and may change in future versions.

Author(s)

Andreas Alfons

References

- Alfons, A., Ates, N.Y. and Groenen, P.J.F. (2021) A robust bootstrap test for mediation analysis. *Organizational Research Methods*, doi: 10.1177/1094428121999096.
- Azzalini, A. and Arellano-Valle, R. B. (2013) Maximum penalized likelihood estimation for skew-normal and skew-t distributions. *Journal of Statistical Planning and Inference*, **143**(2), 419–433.
- Preacher, K.J. and Hayes, A.F. (2004) SPSS and SAS procedures for estimating indirect effects in simple mediation models. *Behavior Research Methods, Instruments, & Computers*, **36**(4), 717–731.
- Preacher, K.J. and Hayes, A.F. (2008) Asymptotic and resampling strategies for assessing and comparing indirect effects in multiple mediator models. *Behavior Research Methods*, **40**(3), 879–891.
- Salibian-Barrera, M. and Van Aelst, S. (2008) Robust model selection using fast and robust bootstrap. *Computational Statistics & Data Analysis*, **52**(12), 5121–5135
- Salibian-Barrera, M. and Zamar, R. (2002) Bootstrapping robust estimates of regression. *The Annals of Statistics*, **30**(2), 556–582.
- Sobel, M.E. (1982) Asymptotic confidence intervals for indirect effects in structural equation models. *Sociological Methodology*, **13**, 290–312.
- Yuan, Y. and MacKinnon, D.P. (2014) Robust mediation analysis based on median regression. *Psychological Methods*, **19**(1), 1–20.
- Zu, J. and Yuan, K.-H. (2010) Local influence and robust procedures for mediation analysis. *Multivariate Behavioral Research*, **45**(1), 1–44.

See Also

`fit_mediation()`
`coef()`, `confint()` and `plot()` methods, `p_value()`
`boot()`, `lmrob()`, `lm()`, `cov_Huber()`, `cov_ML()`

Examples

```
data("BSG2014")

# set seed of the random number generator
set.seed(20211117)

## The results in Alfons et al. (2021) were obtained with an
## older version of the random number generator. To reproduce
## those results, uncomment the two lines below.
# RNGversion("3.5.3")
# set.seed(20150601)

# perform mediation analysis
test <- test_mediation(TeamCommitment ~ m(TaskConflict) + ValueDiversity,
                      data = BSG2014)

summary(test)
```

weights.cov_Huber

Robustness weights of Huber M-estimation of location and scatter

Description

Extract (relative) robustness weights of a Huber M-estimate of location and scatter.

Usage

```
## S3 method for class 'cov_Huber'
weights(object, type = c("consistent", "relative"), ...)
```

Arguments

| | |
|--------|---|
| object | an object inheriting from class " <code>cov_Huber</code> " containing Huber M-estimates of location and scatter. |
| type | a character string specifying the type of robustness weights to be extracted. Possible values are "consistent" and "relative". The former can be used for a robust transformation of the data such that the covariance matrix of the transformed data is Fisher consistent. Observations that are not downweighted in general receive a weight larger than 1. The latter are useful for interpretation, as observations that are not downweighted receive a relative weight of 1. |
| ... | additional arguments are currently ignored. |

Value

A numeric vector containing the requested robustness weights.

Author(s)

Andreas Alfons

References

Zu, J. and Yuan, K.-H. (2010) Local influence and robust procedures for mediation analysis. *Multivariate Behavioral Research*, **45**(1), 1–44.

See Also

[cov_Huber\(\)](#)

Examples

```
data("BSG2014")

# define variables
x <- "ValueDiversity"
y <- "TeamCommitment"
m <- "TaskConflict"

# compute Huber M-estimator
S <- cov_Huber(BSG2014[, c(x, y, m)])
weights(S, type = "relative")
```

weight_plot

Diagnostic plot of robust regression weights

Description

Produce a diagnostic plot of the regression weights from robust mediation analysis. This plot allows to easily detect deviations from normality assumptions such as skewness or heavy tails.

Usage

```
weight_plot(object, ...)

## Default S3 method:
weight_plot(object, outcome = NULL, npoints = 1000, ...)

## S3 method for class 'setup_weight_plot'
weight_plot(object, ...)
```

Arguments

| | |
|---------|---|
| object | an object inheriting from class " <code>fit_mediation</code> " or " <code>test_mediation</code> " containing results from robust mediation analysis. Only mediation analysis objects fitted with the robust MM-estimator are supported. |
| ... | additional arguments to be passed down. |
| outcome | a character vector specifying the outcome variables of the regressions to be included in the plot. This must be a subset of the hypothesized mediators and the dependent variable, or NULL (the default) to include all regressions of the mediation model. |
| npoints | the number of grid points used to evaluate and draw the expected percentages. The default is to use 1000 grid points. |

Details

The horizontal axis contains different weight thresholds, and the vertical axis displays the percentage of observations that have a weight below this threshold. For comparison, a reference line is drawn for the expected percentages under normally distributed errors. Observations with negative and positive residuals are shown separately to make it possible to distinguish between symmetric and asymmetric deviations from normality.

If the plot reveals more downweighted observations than expected, but roughly the same amounts in both tails, the residual distribution is symmetric but with heavy tails. If the plot shows that observations in one tail are downweighted more heavily than those in the other tail, the residual distribution is skewed.

Value

An object inheriting from class "`ggplot`".

Note

The current implementation is a slight hack of `ggplot2` and the `grid` graphics system in order to revert the horizontal axis only in the panels for observations with positive residuals. It is therefore not possible to change the horizontal axis with `scale_x_continuous()`.

The implementation may change in the future if the required functionality becomes available in `ggplot2`.

Author(s)

Andreas Alfons

See Also

`fit_mediation()`, `test_mediation()`, `setup_weight_plot()`
`ci_plot()`, `density_plot()`, `ellipse_plot()`, `plot()`

Examples

```
data("BSG2014")

# run fast-and-robust bootstrap test
test <- test_mediation(BSG2014,
  x = "ValueDiversity",
  y = "TeamCommitment",
  m = "TaskConflict")

# create diagnostic plot of robust regression weights
weight_plot(test) +
  scale_color_manual("", values = c("black", "#00BFC4")) +
  theme(legend.position = "top")

# plot only the regression model for the hypothesized mediator
weight_plot(test, outcome = "TaskConflict") +
  scale_color_manual("", values = c("black", "#00BFC4")) +
  theme(legend.position = "top")
```

Index

- * **datasets**
 - BSG2014, 5
- * **hplot**
 - ci_plot, 8
 - density_plot, 17
 - ellipse_plot, 18
 - plot-methods, 26
 - setup_ci_plot, 33
 - setup_density_plot, 35
 - setup_ellipse_plot, 37
 - setup_weight_plot, 40
 - weight_plot, 50
- * **multivariate**
 - cov_control, 13
 - cov_Huber, 14
 - cov_ML, 16
 - fit_mediation, 21
 - retest, 31
 - test_mediation, 43
- * **package**
 - robmed-package, 2
- * **regression**
 - reg_control, 30
- * **utilities**
 - boot_samples, 4
 - coef.test_mediation, 10
 - confint.test_mediation, 12
 - m, 25
 - p_value, 28
 - summary.test_mediation, 42
 - weights.cov_Huber, 49
- .Random.seed, 30
- autoplot.fit_mediation (plot-methods), 26
- autoplot.test_mediation (plot-methods), 26
- boot, 45, 47, 49
- boot.ci, 13
- boot_samples, 4
- BSG2014, 5
- cbind, 26
- ci_plot, 8, 18, 20, 27, 34, 35, 51
- coef, 13, 29, 49
- coef.boot_test_mediation (coef.test_mediation), 10
- coef.fit_mediation (coef.test_mediation), 10
- coef.test_mediation, 10
- confint, 11, 29, 49
- confint.boot_test_mediation (confint.test_mediation), 12
- confint.sobel_test_mediation (confint.test_mediation), 12
- confint.test_mediation, 12
- cov_control, 13, 14, 15, 23, 46
- cov_Huber, 13, 14, 14, 23–25, 46, 49, 50
- cov_ML, 16, 24, 25, 49
- covariates, 21, 45
- covariates (m), 25
- density_plot, 10, 17, 20, 27, 36, 37, 51
- ellipse_plot, 10, 18, 18, 27, 39, 51
- fit_mediation, 11, 15, 16, 19, 20, 21, 26, 27, 38–41, 45, 46, 48, 49, 51
- ggplot, 9, 17, 20, 27, 51
- lm, 24, 25, 49
- lmrob, 22–25, 30, 46, 49
- lmrob.control, 30
- m, 21, 25, 45
- p_value, 9, 11, 13, 28, 34, 49
- parallel_m (m), 25
- plot, 10, 18, 20, 49, 51

plot-methods, 26
plot.fit_mediation (plot-methods), 26
plot.test_mediation (plot-methods), 26
print.boot_test_mediation
 (test_mediation), 43
print.cov_Huber (cov_Huber), 14
print.cov_ML (cov_ML), 16
print.fit_mediation (fit_mediation), 21
print.sobel_test_mediation
 (test_mediation), 43

reg_control, 22, 30, 46
retest, 31
robmed (test_mediation), 43
robmed-package, 2
rq, 23, 24, 47

scale_x_continuous, 51
serial_m (m), 25
setup_ci_plot, 9, 10, 33
setup_density_plot, 17, 18, 35
setup_ellipse_plot, 20, 37
setup_weight_plot, 40, 51
summary.boot_test_mediation
 (summary.test_mediation), 42
summary.cov_fit_mediation
 (fit_mediation), 21
summary.reg_fit_mediation
 (fit_mediation), 21
summary.sobel_test_mediation
 (summary.test_mediation), 42
summary.test_mediation, 42

test_mediation, 4, 9–13, 15–20, 25–29,
 31–43, 43, 51

weight_plot, 10, 18, 20, 27, 41, 42, 50
weights.cov_Huber, 49