

Package ‘spanish’

May 10, 2019

Type Package

Title Translate Quantities from Strings to Integer and Back. Misc
Functions on Spanish Data

Version 0.4.2

Date 2019-05-10

URL <https://ropenspain.github.io/spanish/>

BugReports <https://github.com/verajosemanuel/spanish/issues>

Imports magrittr, xml2

Description Character vector to numerical translation in Euros from Spanish
spelled monetary quantities. Reverse translation from integer to Spanish.
Upper limit is up to the millions range. Geocoding via Cadastral web site.

License GPL-3

Encoding UTF-8

LazyData true

Collate 'geocode_cadastral.R' 'cadastral_references-data.R'
'to_number.R' 'cantidades-data.R' 'to_words.R' 'utils-pipe.R'
'spanish.R'

RoxygenNote 6.1.1

Suggests testthat, tidyr

NeedsCompilation no

Author Jose Manuel Vera Oteo [aut, cre]

Maintainer Jose Manuel Vera Oteo <vera.josemanuel@gmail.com>

Repository CRAN

Date/Publication 2019-05-10 12:00:03 UTC

R topics documented:

cadastral_references	2
cantidades	3

geocode_cadastral	3
spanish	4
to_number	5
to_words	6

Index	7
--------------	----------

cadastral_references *Cadastral references test data*

Description

Randomly selected data from catastro to test geocode_cadastral function

Usage

```
data(cadastral_references)
```

Format

A data frame.

Source

[Sede Electrónica del Catastro](#)

References

Catastro. Ministerio de Hacienda y función pública. ([Catastro](#))

Examples

```
## Not run:
## source is cadastral reference number ##

geocode_cadastral("0636105UF3403N", parse_files = FALSE)

## Use lapply to geocode cadastral references from dataframe columns.

cadastral_references$new <- lapply(cadastral_references$cadref1, geocode_cadastral)

## separate previously generated "new" data into columns usign tidyr

library(tidyr)
separate(cadastral_references, new, into = c('longitudo', 'latitudo'), sep = ",")

## source is folder. A loop is needed to process each kml file ##

files <- list.files("folder", full.names = T)
```

```

for (f in files) {
  coords <- geocode_cadastral(f, parse_files = TRUE)
  d <- as.data.frame(rbind(d , as.data.frame(coords, stringsAsFactors = F )))
}

# separate lat/lon into columns if you prefer using tidyr
d <- tidyr::separate(coords, into = c("longitude","latitude"), sep = ", " )

## End(Not run)

```

cantidades

Cantidades test data

Description

Randomly generated spanish spelled monetary integers to test to_number function

Usage

```
data(cantidades)
```

Format

A data frame.

Examples

```

to_number("mil trescientos noventa y dos")

## testing provided dataframe: cantidades
cantidades$var3 <- lapply(cantidades$var2, to_number)

```

geocode_cadastral

geocode by longitude and latitude from cadastral references.

Description

Get longitude/latitude from valid cadastral ref. or kml files from catastro.

Arguments

x A valid spanish cadastral reference.
parse_files bool. Default to FALSE. Set TRUE if source are KML files.

Value

A string for longitude/latitude if found. NA if not found.

Warning

You may be banned if many requests in short time are made.

Examples

```
## source is cadastral reference number ##
## Not run:
## geocode_cadastral("0636105UF3403N", parse_files = FALSE)

##"36.5209422288168,-4.89298751473745"

## Use lapply to geocode cadastral references from dataframe columns.

cadastral_references$new <- lapply(cadastral_references$cadref1, geocode_cadastral)

## separate previously generated "new" data into columns usign tidyr

# library(tidyr)
# separate(cadastral_references, new, into = c('longitude','latitude'), sep = ",")

## source is folder. A loop is needed to process each kml file ##

# files <- list.files("folder", full.names = T)

# for (f in files) {
#   coords <- geocode_cadastral(f, parse_files = TRUE)
#   d <- as.data.frame(rbind(d , as.data.frame(coords, stringsAsFactors = F )))
# }

# separate lat/lon into columns if you prefer using tidyr
# d <- tidyr::separate(coords, into = c("longitude","latitude"), sep = ",")

## End(Not run)
```

spanish

spanish: A package for spanish related data functions.

Description

The spanish package provides some functions for spanish data: `to_number()`, `geocode_cadastral()`, `to_words()`

to_number()

Translate spanish spelled quantities into their integer counterparts. Allows you to translate to integer numerical words spelled in spanish. Text must be previously cleaned & removed extraneous words or symbols. Quantities **MUST** be written in a correct Spanish (this is not a grammar tool) The upper limit is up to the millions range. Cents must be removed. (in my TODO list to parse cents part)

to_words()

Translate any integer to character string in spanish spelled quantities. The upper limit is up to the millions range. Cents must be removed. (in my TODO list to parse cents part)

geocode_cadastral()

geocode by longitude and latitude from cadastral references. Get longitude/latitude from valid cadastral ref. or kml files from catastro.

to_number

translate spanish spelled quantities into their integer counterparts.

Description

Allows you to translate to integer numerical words spelled in spanish. Text must be previously cleaned & removed extraneous words or symbols Quantities **MUST** be written in a correct Spanish (this is not a grammar tool) The upper limit is up to the millions range. Cents must be removed.

Arguments

x A spanish spelled number.

Examples

```
to_number("mil trescientos noventa y dos")

# Example table is provided: cantidades
cantidades$var3 <- lapply(cantidades$var2, to_number)
```

`to_words`*From integers to spanish spelled quantities.*

Description

Takes any integer from zero to millions range and returns spanish characters

Arguments

x A valid integer amount.

Value

A string for the same integer number in spanish.

Index

- *Topic **cadastral**
 - geocode_cadastral, 3
- *Topic **cadastre,**
 - geocode_cadastral, 3
- *Topic **currency,**
 - to_number, 5
- *Topic **datasets**
 - cadastral_references, 2
 - cantidades, 3
- *Topic **euros,**
 - to_number, 5
- *Topic **geocoding,**
 - geocode_cadastral, 3
- *Topic **integers,**
 - to_words, 6
- *Topic **latitude,**
 - geocode_cadastral, 3
- *Topic **longitude,**
 - geocode_cadastral, 3
- *Topic **money,**
 - to_number, 5
 - to_words, 6
- *Topic **quantities.**
 - to_words, 6
- *Topic **reference.**
 - geocode_cadastral, 3
- *Topic **spanish,**
 - to_words, 6
- *Topic **translate**
 - to_number, 5

cadastral_references, 2

cantidades, 3

geocode_cadastral, 3

spanish, 4

spanish-package (spanish), 4

to_number, 5

to_words, 6