

Package ‘tidymodels’

March 19, 2022

Title Easily Install and Load the 'Tidymodels' Packages

Version 0.2.0

Description The tidy modeling ``verse'' is a collection of packages for modeling and statistical analysis that share the underlying design philosophy, grammar, and data structures of the tidyverse.

License MIT + file LICENSE

URL <https://tidymodels.tidymodels.org>,
<https://github.com/tidymodels/tidymodels>

BugReports <https://github.com/tidymodels/tidymodels/issues>

Depends R (>= 3.4)

Imports broom (>= 0.7.12), cli (>= 3.2.0), conflicted (>= 1.1.0), dials (>= 0.1.0), dplyr (>= 1.0.8), ggplot2 (>= 3.3.5), hardhat (>= 0.2.0), infer (>= 1.0.0), modeldata (>= 0.1.1), parsnip (>= 0.2.1), purrr (>= 0.3.4), recipes (>= 0.2.0), rlang (>= 1.0.2), rsample (>= 0.1.1), rstudioapi (>= 0.13), tibble (>= 3.1.6), tidyr (>= 1.2.0), tune (>= 0.2.0), workflows (>= 0.2.5), workflowsets (>= 0.2.1), yardstick (>= 0.0.9)

Suggests covr, glue, knitr, rmarkdown, testthat (>= 3.0.0), xml2

VignetteBuilder knitr

Config/Needs/website tidyverse/tidytemplate

Encoding UTF-8

RoxygenNote 7.1.2

Config/testthat/edition 3

NeedsCompilation no

Author Max Kuhn [aut, cre],
Hadley Wickham [aut],
RStudio [cph, fnd]

Maintainer Max Kuhn <max@rstudio.com>

Repository CRAN

Date/Publication 2022-03-19 21:30:02 UTC

R topics documented:

pkg_deps	2
tag_show	2
tidymodels_conflicts	3
tidymodels_packages	3
tidymodels_prefer	4
tidymodels_update	4

Index

6

pkg_deps	<i>List all dependencies</i>
-----------------	------------------------------

Description

List all dependencies

Usage

```
pkg_deps(x = "tidymodels", recursive = FALSE)
```

Arguments

- x A character string for the packages being evaluated.
- recursive If TRUE, will also list all dependencies of tidymodels packages.

tag_show	<i>Facilities for loading and updating other packages</i>
-----------------	---

Description

The tidymodels metapackage contains a set of tags for specific topics in modeling and analysis. These can be used to load packages in groups.

Usage

```
tag_show()  
tag_attach(tag)  
tag_update(tag)
```

Arguments

tag	A character string for the tag. Current options are: 'Bayesian analysis', 'deep learning', 'ensembles', 'extra models', 'extra recipes', 'feature engineering', 'interpretation', 'parallel processing', 'parameter tuning', 'resampling', 'text analysis', 'time series', and 'visualization'.
-----	---

Examples

```
tag_show()
```

`tidymodels_conflicts` *Conflicts between the tidymodels and other packages*

Description

This function lists all the conflicts between packages in the tidymodels and other packages that you have loaded.

Usage

```
tidymodels_conflicts()
```

Details

There are four conflicts that are deliberately ignored: `intersect`, `union`, `setequal`, and `setdiff` from `dplyr`. These functions make the base equivalents generic, so shouldn't negatively affect any existing code.

Examples

```
tidymodels_conflicts()
```

`tidymodels_packages` *List all packages in the tidymodels*

Description

List all packages in the tidymodels

Usage

```
tidymodels_packages(include_self = TRUE)
```

Arguments

include_self	Include tidymodels in the list?
--------------	---------------------------------

Examples

```
tidymodels_packages()
```

tidymodels_prefer	<i>Resolve conflicts between tidymodels packages and others</i>
-------------------	---

Description

`tidymodels_prefer()` uses the conflicted package to handle common conflicts with tidymodels and other packages.

Usage

```
tidymodels_prefer(quiet = TRUE)
```

Arguments

quiet	If TRUE, all output will be suppressed
-------	--

Details

The list of conflicts includes about a dozen that are known issues with other packages.

Examples

```
tidymodels_prefer(quiet = FALSE)
```

tidymodels_update	<i>Update tidymodels packages</i>
-------------------	-----------------------------------

Description

This will check to see if all tidymodels packages (and optionally, their dependencies) are up-to-date, and will install after an interactive confirmation.

Usage

```
tidymodels_update(pkg = "tidymodels", recursive = FALSE, ...)
```

Arguments

pkg	A character string for the model being updated.
recursive	If TRUE, will also check all dependencies of tidymodels packages.
...	Extra arguments to pass to <code>utils::install.packages()</code>

Value

Nothing is returned but a message is printed to the console about which packages (if any) should be installed along with code to do so.

Examples

```
## Not run:  
tidymodels_update()  
  
## End(Not run)
```

Index

pkg_deps, [2](#)
tag_attach (tag_show), [2](#)
tag_show, [2](#)
tag_update (tag_show), [2](#)
tags (tag_show), [2](#)
tidymodels_conflicts, [3](#)
tidymodels_packages, [3](#)
tidymodels_prefer, [4](#)
tidymodels_update, [4](#)
utils::install.packages(), [4](#)