Package 'waffle'

January 7, 2017

Type Package
Title Create Waffle Chart Visualizations in R
Version 0.7.0
Date 2017-01-07
Maintainer Bob Rudis <bob@rud.is>
Description Square pie charts (a.k.a. waffle charts) can be used to communicate parts of a whole for categorical quantities. To emulate the percentage view of a pie chart, a 10x10 grid should be used with each square representing 1% of the total. Modern uses of waffle charts do not necessarily adhere to this rule and can be created with a grid of any rectangular shape. Best practices suggest keeping the number of categories small, just as should be done when creating pie charts. Tools are provided to create waffle charts as well as stitch them together, and to use glyphs for making isotype pictograms.

URL https://github.com/hrbrmstr/waffle/tree/cran

BugReports https://github.com/hrbrmstr/waffle/issues

Suggests testthat

Depends R (>= 3.2.0), ggplot2 (>= 2.0.0)

License GPL (≥ 2)

Imports RColorBrewer, grid, gridExtra, gtable, extrafont

RoxygenNote 5.0.1

NeedsCompilation no

Author Bob Rudis [aut, cre], Dave Gandy [aut] (Font Awesome)

Repository CRAN

Date/Publication 2017-01-07 15:59:43

R topics documented:

a_grep							 •												
a_list						•	 •			•				•		•		•	•
ron																			
waffle							 •												•

Index

waffle-package A package to make w

A package to make waffle charts (square pie charts) in R.

Description

For glyphs:

Font Awesome by Dave Gandy - http://fontawesome.io License: SIL OFL 1.1 URL: http://scripts.sil.org/OFL

fa_grep

Search FontAwesome names for a pattern

Description

Search FontAwesome names for a pattern

Usage

fa_grep(pattern)

Arguments

pattern pattern to search for in the names of FontAwesome fonts

fa_list	List all FontAwesome names	

Description

List all FontAwesome names

Usage

fa_list()

iron

Description

Left-align the waffle plots by x-axis. Use the pad parameter in waffle to pad each plot to the max width (num of squares), otherwise the plots will be scaled.

Usage

iron(...)

Arguments

... one or more waffle plots

Examples

```
parts <- c(80, 30, 20, 10)
w1 <- waffle(parts, rows=8)
w2 <- waffle(parts, rows=8)
w3 <- waffle(parts, rows=8)
# print chart
## iron(w1, w2, w3)</pre>
```

waffle

Make waffle (square pie) charts

Description

Given a named vector, this function will return a ggplot object that represents a waffle chart of the values. The individual values will be summed up and each that will be the total number of squares in the grid. You can perform appropriate value transformation ahead of time to get the desired waffle layout/effect.

Usage

```
waffle(parts, rows = 10, keep = TRUE, xlab = NULL, title = NULL,
colors = NA, size = 2, flip = FALSE, reverse = FALSE, equal = TRUE,
pad = 0, use_glyph = FALSE, glyph_size = 12, legend_pos = "right")
```

Arguments

parts	named vector of values to use for the chart
rows	number of rows of blocks
keep	keep factor levels (i.e. for consistent legends across waffle plots)
xlab	text for below the chart. Highly suggested this be used to give the "1 sq == xyz " relationship if it's not obvious
title	chart title
colors	exactly the number of colors as values in parts. If omitted, Color Brewer "Set2" colors are used.
size	width of the separator between blocks (defaults to 2)
flip	flips x & y axes
reverse	reverses the order of the data
equal	by default, waffle uses coord_equal; this can cause layout problems, so you an use this to disable it if you are using ggsave or knitr to control output sizes (or manually sizing the chart)
pad	how many blocks to right-pad the grid with
use_glyph	use specified FontAwesome glyph
glyph_size	size of the FontAwesome font
legend_pos	position of legend

Details

If the vector is not named or only partially named, capital letters will be used instead. It is highly suggested that you limit the number of elements to plot, just like you should if you ever got wasted and decided that a regular pie chart was a good thing to create and then decide to be totally evil and make one to pollute this beautiful world of ours.

Chart title and x-axis labels are optional, especially if you'll just be exporting to another program for use/display.

If you specify a string (vs FALSE) to use_glyph the function will map the input to a FontAwesome glyph name and use that glyph for the tile instead of a block (making it more like an isotype pictogram than a waffle chart). You'll need to actually install FontAwesome and use the extrafont package (https://github.com/wch/extrafont) to be able to use the FontAwesome glyphs. Sizing is also up to the user since fonts do not automatically scale with graphic resize.

Glyph idea inspired by Ruben C. Arslan (@_r_c_a)

Examples

```
parts <- c(80, 30, 20, 10)
chart <- waffle(parts, rows=8)
# print(chart)
# library(extrafont)
# waffle(parts, rows=8, use_glyph="shield")</pre>
```

waffle

```
parts <- c(One=80, Two=30, Three=20, Four=10)
chart <- waffle(parts, rows=8)
# print(chart)</pre>
```

Index

fa_grep,2 fa_list,2

iron,3

waffle, 3
waffle-package, 2