

Package ‘ypr’

July 3, 2021

Title Yield Per Recruit

Version 0.5.2

Description An implementation of equilibrium-based yield per recruit methods. Yield per recruit methods can used to estimate the optimal yield for a fish population as described by Walters and Martell (2004) <isbn:0-691-11544-3>. The yield can be based on the number of fish caught (or harvested) or biomass caught for all fish or just large (trophy) individuals.

License MIT + file LICENSE

URL <https://github.com/poissonconsulting/ypr>

BugReports <https://github.com/poissonconsulting/ypr/issues>

Depends R (>= 3.4)

Imports chk, ggplot2, graphics, lifecycle, purrr, scales, stats, tools, yesno

Suggests covr, knitr, rmarkdown, rstudioapi, testthat, tidyverse

VignetteBuilder knitr

ByteCompile true

Encoding UTF-8

Language en-US

LazyData true

RoxygenNote 7.1.1

NeedsCompilation no

Author Joe Thorley [aut, cre] (<<https://orcid.org/0000-0002-7683-4592>>),
Poisson Consulting [cph, fnd]

Maintainer Joe Thorley <joe@poissonconsulting.ca>

Repository CRAN

Date/Publication 2021-07-03 04:40:02 UTC

R topics documented:

adams_bt_03	3
as_ypr_population	3
as_ypr_populations	4
chilliwack_bt_05	5
kootenay_bt_13	5
kootenay_rb	6
kootenay_rb_13	7
plot.ypr_population	7
quesnel_bt	8
quesnel_lt	9
quesnel_rb	9
update.ypr_population	10
update.ypr_populations	11
ypr_age_at_length	12
ypr_detabulate_parameters	12
ypr_exploitation	13
ypr_length_at_age	14
ypr_optimize	14
ypr_plot_biomass	15
ypr_plot_fish	16
ypr_plot_schedule	17
ypr_plot_sr	17
ypr_plot_yield	18
ypr_plot_yield.ypr_population	19
ypr_plot_yield.ypr_populations	20
ypr_population	21
ypr_populations	23
ypr_populations_expand	24
ypr_population_names	24
ypr_report	25
ypr_schedule	26
ypr_sr	26
ypr_tabulate_biomass	27
ypr_tabulate_fish	28
ypr_tabulate_parameters	28
ypr_tabulate_sr	29
ypr_tabulate_yield	30
ypr_tabulate_yields	32
ypr_yield	33
ypr_yields	34

adams_bt_03

Adams Lake Bull Trout Population Parameters (2003)

Description

The population parameters for Bull Trout in Adams Lake from Bison et al (2003)

Usage

```
adams_bt_03
```

Format

An object of class [ypr_population\(\)](#).

References

Bison, R., O'Brien, D., and Martell, S.J.D. 2003. An Analysis of Sustainable Fishing Options for Adams Lake Bull Trout Using Life History and Telemetry Data. BC Ministry of Water Land and Air Protection, Kamloops, B.C.

Examples

```
adams_bt_03  
ypr_plot_yield(adams_bt_03)
```

as_ypr_population

Coerce to a Population Parameter Object

Description

Coerce to a Population Parameter Object

Usage

```
as_ypr_population(x, ...)  
  
## S3 method for class 'data.frame'  
as_ypr_population(x, ...)
```

Arguments

x The object to coerce.
... Unused parameters.

Methods (by class)

- `data.frame`: Coerce data frame to `ypr_population`

Examples

```
as_ypr_population(as.data.frame(ypr_population()))
```

`as_ypr_populations` *Coerce to a Populations Parameter Object*

Description

Coerce to a Populations Parameter Object

Usage

```
as_ypr_populations(x, ...)
## S3 method for class 'data.frame'
as_ypr_populations(x, ...)
```

Arguments

- | | |
|------------------|-----------------------|
| <code>x</code> | The object to coerce. |
| <code>...</code> | Unused parameters. |

Methods (by class)

- `data.frame`: Coerce data frame to `ypr_populations`

Examples

```
as_ypr_populations(as.data.frame(ypr_populations(Rk = c(3, 4))))
```

chilliwack_bt_05	<i>Chilliwack Lake Bull Trout Populations Parameters (2005)</i>
------------------	---

Description

The populations parameters for Bull Trout in Chilliwack Lake from Taylor (2005)

Usage

```
chilliwack_bt_05
```

Format

An object of class [ypr_populations\(\)](#).

References

Taylor, J.L. 2005. Sustainability of the Chilliwack Lake Char Fishery. Ministry of Water, Land and Air Protection, Surrey, B.C.

Examples

```
chilliwack_bt_05
yield <- ypr_tabulate_yield(chilliwack_bt_05, type = "optimal")
yield$pi <- round(yield$pi, 2)
yield <- yield[c("Llo", "Hm", "Rk", "pi")]
yield <- tidyrr::spread(yield, Rk, pi)
yield <- yield[order(-yield$Hm), ]
yield
## Not run:
ypr_plot_yield(chilliwack_bt_05, plot_values = FALSE) +
  ggplot2::facet_grid(Rk ~ Hm) +
  ggplot2::aes(group = Llo, linetype = Llo)

## End(Not run)
```

kootenay_bt_13	<i>Kootenay Lake Bull Trout Population Parameters (2013)</i>
----------------	--

Description

The population parameters for Bull Trout in Kootenay Lake from Andrusak and Thorley (2013)

Usage

```
kootenay_bt_13
```

Format

An object of class [ypr_population\(\)](#).

Details

The estimates should not be used for management.

References

Andrusak, G.F., and Thorley, J.L. 2013. Kootenay Lake Exploitation Study: Fishing and Natural Mortality of Large Rainbow Trout and Bull Trout: 2013 Annual Report. A Poisson Consulting Ltd. and Redfish Consulting Ltd. Report, Habitat Conservation Trust Foundation, Victoria, BC.

Examples

```
kootenay_bt_13  
ypr_plot_yield(kootenay_bt_13)
```

kootenay_rb

Kootenay Lake Rainbow Trout Population Parameters

Description

The population parameters for Rainbow Trout in Kootenay Lake.

Usage

```
kootenay_rb
```

Format

An object of class [ypr_population\(\)](#).

Details

The estimates are liable to change and should not be used for management.

References

Thorley, J.L., and Andrusak, G.F. 2017. The fishing and natural mortality of large, piscivorous Bull Trout and Rainbow Trout in Kootenay Lake, British Columbia (2008–2013). PeerJ 5: e2874. doi:10.7717/peerj.2874.

Examples

```
kootenay_rb  
ypr_plot_yield(kootenay_rb)
```

kootenay_rb_13

Kootenay Lake Rainbow Trout Population Parameters (2013)

Description

The population parameters for Rainbow Trout in Kootenay Lake from Andrusak and Thorley (2013)

Usage

```
kootenay_rb_13
```

Format

An object of class [ypr_population\(\)](#).

Details

The estimates should not be used for management.

References

Andrusak, G.F., and Thorley, J.L. 2013. Kootenay Lake Exploitation Study: Fishing and Natural Mortality of Large Rainbow Trout and Bull Trout: 2013 Annual Report. A Poisson Consulting Ltd. and Redfish Consulting Ltd. Report, Habitat Conservation Trust Foundation, Victoria, BC.

See Also

[kootenay_rb\(\)](#)

Examples

```
kootenay_rb_13  
ypr_plot_yield(kootenay_rb_13)
```

`plot.ypr_population` *Plot Population Schedule*

Description

Plot Population Schedule

Usage

```
## S3 method for class 'ypr_population'  
plot(x, type = "b", ...)
```

Arguments

- x The population to plot.
- type A string specifying the plot type. Possible values include 'b', 'p' and 'l'.
- ... Additional arguments passed to [graphics::plot](#) function.

Value

An invisible copy of the original object.

See Also

[graphics::plot](#), [ypr_population\(\)](#) and [ypr_tabulate_schedule\(\)](#)

Examples

```
## Not run:
plot(ypr_population())

## End(Not run)
```

quesnel_bt

Quesnel Lake Bull Trout Population Parameters

Description

The population parameters for Bull Trout in Quesnel Lake, BC.

Usage

`quesnel_bt`

Format

An object of class [ypr_population\(\)](#).

Details

The estimates are liable to change and should not be used for management.

Examples

```
quesnel_bt
ypr_plot_yield(quesnel_bt)
```

*quesnel_lt**Quesnel Lake Lake Trout Population Parameters*

Description

The population parameters for Lake Trout in Quesnel Lake, BC.

Usage

```
quesnel_lt
```

Format

An object of class [ypr_population\(\)](#).

Details

The estimates are liable to change and should not be used for management.

Examples

```
quesnel_lt  
ypr_plot_yield(quesnel_lt)
```

*quesnel_rb**Quesnel Lake Rainbow Trout Population Parameters*

Description

The population parameters for Rainbow Trout in Quesnel Lake, BC.

Usage

```
quesnel_rb
```

Format

An object of class [ypr_population\(\)](#).

Details

The estimates are liable to change and should not be used for management.

Examples

```
quesnel_rb  
ypr_plot_yield(quesnel_rb)
```

`update.ypr_population` *Update Population Parameters*

Description

Updates an object of class [ypr_population\(\)](#).

Usage

```
## S3 method for class 'ypr_population'  
update(object, ...)  
  
ypr_population_update(population, ...)
```

Arguments

<code>object</code>	The populations or populations.
<code>...</code>	One or more of the arguments from <code>ypr_population()</code> .
<code>population</code>	An object of class ypr_population() .

Value

An object of class `ypr_population`.

Methods (by generic)

- `update`: Update Population Parameters

See Also

[ypr_population\(\)](#)

Examples

```
ypr_population_update(ypr_population(), Rk = 2.5)
```

```
update.ypr_populations
    Update Population Parameters
```

Description

Updates an object of class [ypr_population\(\)](#).

Usage

```
## S3 method for class 'ypr_populations'
update(object, ...)

ypr_populations_update(populations, ...)
```

Arguments

object	The populations or populations.
...	One or more of the arguments from ypr_population() .
populations	An object of class ypr_populations() .

Value

An object of class [ypr_population](#).

Methods (by generic)

- update: Update Populations Parameters

See Also

[ypr_population\(\)](#)

Examples

```
ypr_populations_update(ypr_populations(Rk = c(2.5, 4)), Rk = 2.5)
```

`ypr_age_at_length` *Age At Length*

Description

Age At Length

Usage

```
ypr_age_at_length(population, length)
```

Arguments

- | | |
|-------------------------|---|
| <code>population</code> | An object of class ypr_population() . |
| <code>length</code> | A numeric vector of the length (cm). |

Value

A double vector of the lengths.

Examples

```
ypr_age_at_length(ypr_population(), seq(0, 100, by = 10))
```

`ypr_detabulate_parameters`
Detabulate Population Parameters

Description

Detabulate Population Parameters

Usage

```
ypr_detabulate_parameters(x)
```

Arguments

- | | |
|----------------|---|
| <code>x</code> | A data frame with columns Parameter and Value specifying one or more parameters and their values. |
|----------------|---|

Value

An object of class [ypr_population\(\)](#)

See Also[ypr_tabulate_parameters\(\)](#)**Examples**

```
ypr_detabulate_parameters(ypr_tabulate_parameters(ypr_population()))
```

ypr_exploitation *Exploitation Probability*

Description

Converts capture probabilities into exploitation probabilities based on the release and handling mortality probabilities where the probability of exploitation includes handling mortalities. The calculation assumes that a released fish cannot be recaptured in the same year.

Usage

```
ypr_exploitation(population, pi = population$pi)
```

Arguments

- population An object of class [ypr_population\(\)](#).
pi A vector of capture probabilities to calculate the exploitation probabilities for.

Details

In the case of no release (or 100% handling mortalities) the exploitation probability is identical to the capture probability. Otherwise it is less.

Value

A vector of exploitation probabilities.

See Also[ypr_population\(\)](#)**Examples**

```
ypr_exploitation(ypr_population(pi = 0.4))
ypr_exploitation(ypr_population(pi = 0.4, rho = 0.6, Hm = 0.2))
```

`ypr_length_at_age` *Length At Age*

Description

Length At Age

Usage

```
ypr_length_at_age(population, age)
```

Arguments

- | | |
|-------------------------|---|
| <code>population</code> | An object of class ypr_population() . |
| <code>age</code> | A numeric vector of the age (yr). |

Value

A double vector of the lengths.

Examples

```
ypr_length_at_age(ypr_population(), seq(0, 5, by = 0.5))
```

`ypr_optimize` *Optimize Capture*

Description

Finds the interval annual capture probability (*pi*) that maximises the yield for a given population.

Usage

```
ypr_optimize(population, Ly = 0, harvest = TRUE, biomass = FALSE)
```

Arguments

- | | |
|-------------------------|--|
| <code>population</code> | An object of class ypr_population() . |
| <code>Ly</code> | The minimum length (trophy) fish to consider when calculating the yield (cm). |
| <code>harvest</code> | A flag specifying whether to calculate the yield for harvested fish or captures. |
| <code>biomass</code> | A flag specifying whether to calculate the yield in terms of the biomass versus number of individuals. |

Value

The interval annual capture probability (*pi*) that maximises the yield.

See Also

[ypr_population\(\)](#) and [ypr_yield\(\)](#)

Examples

```
ypr_optimize(ypr_population())
```

ypr_plot_biomass *Plot Biomass*

Description

Produces a frequency histogram of the total fish 'Biomass' or 'Eggs' deposition by 'Age' class.

Usage

```
ypr_plot_biomass(population, y = "Biomass", color = NULL)
```

Arguments

- | | |
|------------|---|
| population | An object of class ypr_population() . |
| y | A string of the term on the y-axis. |
| color | A string of the color around each bar (or NULL). |

Value

A ggplot2 object.

See Also

[ypr_population\(\)](#) and [ggplot2::geom_histogram\(\)](#)

Examples

```
ypr_plot_biomass(ypr_population(), color = "white")
```

`ypr_plot_fish` *Plot Fish*

Description

Produces a frequency histogram of the number of fish in the 'Survivors', 'Spawners', 'Caught', 'Harvested' or 'Released' categories by 'Length', 'Age' or 'Weight' class.

Usage

```
ypr_plot_fish(
  population,
  x = "Age",
  y = "Survivors",
  percent = FALSE,
  binwidth = 1L,
  color = NULL
)
```

Arguments

<code>population</code>	An object of class ypr_population() .
<code>x</code>	The object to coerce.
<code>y</code>	A string of the term on the y-axis.
<code>percent</code>	A flag specifying whether to plot the number of fish as a percent or frequency (the default).
<code>binwidth</code>	A positive integer of the width of the bins for grouping.
<code>color</code>	A string of the color around each bar (or NULL).

Value

A ggplot2 object.

See Also

[ypr_population\(\)](#) and [ggplot2::geom_histogram\(\)](#)

Examples

```
ypr_plot_fish(ypr_population(), color = "white")
```

ypr_plot_schedule *Plot Population Schedule Terms*

Description

Produces a bivariate line plot of two schedule terms.

Usage

```
ypr_plot_schedule(population, x = "Age", y = "Length")
```

Arguments

- | | |
|------------|---|
| population | An object of class ypr_population() . |
| x | A string of the term on the x-axis. |
| y | A string of the term on the y-axis. |

Value

A ggplot2 object.

See Also

[ypr_population\(\)](#) and [ypr_tabulate_schedule\(\)](#)

Examples

```
ypr_plot_schedule(ypr_population())
```

ypr_plot_sr *Plot Stock-Recruitment Curve*

Description

Plot Stock-Recruitment Curve

Usage

```
ypr_plot_sr(  
  population,  
  Ly = 0,  
  harvest = TRUE,  
  biomass = FALSE,  
  plot_values = TRUE  
)
```

Arguments

<code>population</code>	An object of class ypr_population() .
<code>Ly</code>	The minimum length (trophy) fish to consider when calculating the yield (cm).
<code>harvest</code>	A flag specifying whether to calculate the yield for harvested fish or captures.
<code>biomass</code>	A flag specifying whether to calculate the yield in terms of the biomass versus number of individuals.
<code>plot_values</code>	A flag specifying whether to plot the actual and optimal values.

Value

A ggplot2 object.

See Also

[ypr_population\(\)](#) and [ypr_sr\(\)](#)

Examples

```
ypr_plot_sr(ypr_population(Rk = 10))
ypr_plot_sr(ypr_population(Rk = 10, BH = 0L))
```

<code>ypr_plot_yield</code>	<i>Plot Yield by Capture</i>
-----------------------------	------------------------------

Description

Plots the 'Yield', 'Age', 'Length', 'Weight', 'Effort', or 'YPUE' by the annual interval capture probability.

Usage

```
ypr_plot_yield(object, ...)
```

Arguments

<code>object</code>	The populations or populations.
...	Unused parameters.

Value

A ggplot2 object.

See Also

[ypr_population\(\)](#) and [ypr_yields\(\)](#)

Examples

```
ypr_plot_yield(ypr_population())
```

ypr_plot_yield.ypr_population
Plot Yield by Exploitation/Capture Probability

Description

Plots the 'Yield', 'Age', 'Length', 'Weight', 'Effort', or 'YPUE' by the annual interval exploitation/capture probability.

Usage

```
## S3 method for class 'ypr_population'
ypr_plot_yield(
  object,
  y = "Yield",
  pi = seq(0, 1, length.out = 100),
  Ly = 0,
  harvest = TRUE,
  biomass = FALSE,
  u = harvest,
  plot_values = TRUE,
  ...
)
```

Arguments

object	The populations or populations.
y	A string of the term on the y-axis.
pi	A vector of probabilities of capture to calculate the yield for.
Ly	The minimum length (trophy) fish to consider when calculating the yield (cm).
harvest	A flag specifying whether to calculate the yield for harvested fish or captures.
biomass	A flag specifying whether to calculate the yield in terms of the biomass versus number of individuals.
u	A flag specifying whether to plot the exploitation rate as opposed to the capture rate.
plot_values	A flag specifying whether to plot the actual and optimal values.
...	Unused parameters.

Value

A ggplot2 object.

See Also

[ypr_population\(\)](#) and [ypr_yields\(\)](#)

Examples

```
ypr_plot_yield(ypr_population())
```

ypr_plot_yield.ypr_populations
Plot Yield by Exploitation/Capture Probability

Description

Plots the 'Yield', 'Age', 'Length', 'Weight', 'Effort', or 'YPUE' by the annual interval exploitation/capture probability.

Usage

```
## S3 method for class 'ypr_populations'
ypr_plot_yield(
  object,
  y = "Yield",
  pi = seq(0, 1, length.out = 100),
  Ly = 0,
  harvest = TRUE,
  biomass = FALSE,
  u = harvest,
  plot_values = TRUE,
  ...
)
```

Arguments

<code>object</code>	The populations or populations.
<code>y</code>	A string of the term on the y-axis.
<code>pi</code>	A vector of probabilities of capture to calculate the yield for.
<code>Ly</code>	The minimum length (trophy) fish to consider when calculating the yield (cm).
<code>harvest</code>	A flag specifying whether to calculate the yield for harvested fish or captures.
<code>biomass</code>	A flag specifying whether to calculate the yield in terms of the biomass versus number of individuals.
<code>u</code>	A flag specifying whether to plot the exploitation rate as opposed to the capture rate.
<code>plot_values</code>	A flag specifying whether to plot the actual and optimal values.
<code>...</code>	Unused parameters.

Value

A ggplot2 object.

See Also

[ypr_populations\(\)](#) and [ypr_yields\(\)](#)

Examples

```
## Not run:  
ypr_plot_yield(ypr_populations(Rk = c(2.5, 4.6), Llo = c(0, 60)), plot_values = FALSE) +  
  ggplot2::facet_wrap(~Llo) +  
  ggplot2::aes_string(group = "Rk", color = "Rk") +  
  ggplot2::scale_color_manual(values = c("black", "blue"))  
  
ypr_plot_yield(ypr_populations(Rk = c(2.5, 4.6), Llo = c(0, 60))) +  
  ggplot2::facet_grid(Rk ~ Llo)  
  
## End(Not run)
```

ypr_population *Population Parameters*

Description

Generates an object of class `ypr_population`.

Usage

```
ypr_population(  
  tmax = 20L,  
  k = 0.15,  
  Linf = 100,  
  t0 = 0,  
  k2 = 0.15,  
  Linf2 = 100,  
  L2 = 1000,  
  Wb = 3,  
  Ls = 50,  
  Sp = 100,  
  es = 1,  
  Sm = 0,  
  fb = 1,  
  tR = 1L,  
  BH = 1L,  
  Rk = 3,  
  n = 0.2,  
  nL = 0.2,  
  Ln = 1000,  
  Lv = 50,  
  Vp = 100,
```

```

Llo = 0,
Lup = 1000,
Nc = 0,
pi = 0.2,
rho = 0,
Hm = 0,
Rmax = 1,
Wa = 0.01,
fa = 1,
q = 0.1
)

```

Arguments

tmax	The maximum age (yr).
k	The VB growth coefficient (yr-1).
Linf	The VB mean maximum length (cm).
t0	The (theoretical) age at zero length (yr).
k2	The VB growth coefficient after length L2 (yr-1).
Linf2	The VB mean maximum length after length L2 (cm).
L2	The length (or age if negative) at which growth switches from the first to second phase (cm or yr).
Wb	The weight (as a function of length) scaling exponent.
Ls	The length (or age if negative) at which 50 % mature (cm or yr).
Sp	The maturity (as a function of length) power.
es	The annual probability of a mature fish spawning.
Sm	The spawning mortality probability.
fb	The fecundity (as a function of weight) scaling exponent.
tR	The age from which survival is density-independent (yr).
BH	Recruitment follows a Beverton-Holt (1) or Ricker (0) relationship.
Rk	The lifetime spawners per spawner at low density.
n	The annual interval natural mortality rate from age tR.
nL	The annual interval natural mortality rate from length Ln.
Ln	The length (or age if negative) at which the natural mortality rate switches from n to nL (cm or yr).
Lv	The length (or age if negative) at which 50 % vulnerable to harvest (cm or yr).
Vp	The vulnerability to harvest (as a function of length) power.
Llo	The lower harvest slot length (cm).
Lup	The upper harvest slot length (cm).
Nc	The slot limits non-compliance probability.
pi	The annual capture probability.

rho	The release probability.
Hm	The hooking mortality probability.
Rmax	The number of recruits at the carrying capacity (ind).
Wa	The (extrapolated) weight of a 1 cm individual (g).
fa	The (theoretical) fecundity of a 1 g female (eggs).
q	The catchability (annual probability of capture) for a unit of effort.

Value

An object of class `ypr_population`.

See Also

`ypr_population_update()`, `ypr_tabulate_schedule()`, `ypr_yield()` and `ypr_optimize()`.

Examples

```
ypr_population(k = 0.1, Linf = 90)
```

ypr_populations *Populations*

Description

Populations

Usage

```
ypr_populations(..., expand = TRUE)
```

Arguments

...	Unused parameters.
expand	A flag specifying whether to expand parameter combinations.

Value

A list of `ypr_population()` objects

See Also

`ypr_population()`

Examples

```
ypr_populations(Rk = c(2.5, 4.6), Hm = c(0.2, 0.05))
```

```
ypr_populations_expand
```

Expand Populations

Description

An object of class [ypr_population\(\)](#) of all unique combinations of parameter values.

Usage

```
ypr_populations_expand(populations)
```

Arguments

`populations` An object of class [ypr_populations\(\)](#).

Value

An object of class [ypr_population](#).

See Also

[ypr_population\(\)](#)

Examples

```
ypr_populations_expand(ypr_populations(Rk = c(2.5, 4, 2.5), Hm = c(0.1, 0.2, 0.1)))
```

```
ypr_population_names  Population Names
```

Description

Population Names

Usage

```
ypr_population_names(populations)
```

Arguments

`populations` An object of class [ypr_populations\(\)](#).

Value

A character vector of the unique population names.

Examples

```
ypr_population_names(ypr_populations(Rk = c(2.5, 3, 2.5), expand = FALSE))
```

ypr_report

Report

Description

Creates an Rmd file that can be used to generate a report.

Usage

```
ypr_report(  
  population,  
  Ly = 0,  
  harvest = TRUE,  
  biomass = FALSE,  
  title = "Population Report",  
  description = "",  
  date = Sys.Date(),  
  file = "report",  
  view = FALSE,  
  ask = TRUE  
)
```

Arguments

population	An object of class ypr_population() .
Ly	The minimum length (trophy) fish to consider when calculating the yield (cm).
harvest	A flag specifying whether to calculate the yield for harvested fish or captures.
biomass	A flag specifying whether to calculate the yield in terms of the biomass versus number of individuals.
title	A string of the report title.
description	A string describing the population.
date	A date of the report date.
file	A string of the path to the file (without the extension).
view	A flag specifying whether to view the report (after rendering it to html).
ask	A flag specifying whether to ask before overwriting or creating a file.

Value

An invisible character vector of the contents of the file.

Examples

```
ypr_report(ypr_population(), file = tempfile(), ask = FALSE)
```

ypr_schedule	<i>Life-History Schedule</i>
--------------	------------------------------

Description

Generates the life-history schedule by age for a population.

Usage

```
ypr_schedule(population)
```

```
ypr_tabulate_schedule(population)
```

Arguments

population An object of class [ypr_population\(\)](#).

Value

A tibble of the life-history schedule by age.

Functions

- **ypr_schedule**: Tabulate Schedule (Deprecated)

See Also

[ypr_population\(\)](#)

Examples

```
ypr_tabulate_schedule(ypr_population())
```

ypr_sr	<i>Stock-Recruitment Parameters</i>
--------	-------------------------------------

Description

Returns a single rowed data frame of the SR parameters:

alpha Survival from egg to age tR at low density

beta Density-dependence

Rk Lifetime spawners per spawner at low density

phi Lifetime eggs deposited per recruit at unfished equilibrium

phiF Lifetime eggs deposited per recruit at the fished equilibrium

- R0** Age tR recruits at the unfished equilibrium
- R0F** Age tR recruits at the fished equilibrium
- S0** Spawners at the unfished equilibrium
- S0F** Spawners at the fished equilibrium

Usage

```
ypr_sr(population)
```

Arguments

population An object of class [ypr_population\(\)](#).

Value

A data frame of the SR parameters.

Examples

```
ypr_sr(ypr_population()) # Beverton-Holt  
ypr_sr(ypr_population(BH = 0L)) # Ricker
```

ypr_tabulate_biomass *Tablulate Biomass (and Eggs)*

Description

Produces a data frame of the 'Weight' and 'Fecundity' and the number of 'Survivors' and 'Spawners' and the total 'Biomass' and 'Eggs' by 'Age' class.

Usage

```
ypr_tabulate_biomass(population)
```

Arguments

population An object of class [ypr_population\(\)](#).

Value

A data frame

See Also

Other tabulate: [ypr_tabulate_fish\(\)](#), [ypr_tabulate_parameters\(\)](#), [ypr_tabulate_sr\(\)](#), [ypr_tabulate_yields\(\)](#), [ypr_tabulate_yield\(\)](#)

Examples

```
ypr_tabulate_biomass(ypr_population())
```

`ypr_tabulate_fish` *Tabulate Fish Numbers*

Description

Produces a data frame of the number of fish in the 'Survivors', 'Spawners', 'Caught', 'Harvested', 'Released' and 'HandlingMortalities' categories by 'Length', 'Age' or 'Weight' class.

Usage

```
ypr_tabulate_fish(population, x = "Age", binwidth = 1L)
```

Arguments

- | | |
|-------------------------|---|
| <code>population</code> | An object of class ypr_population() . |
| <code>x</code> | The object to coerce. |
| <code>binwidth</code> | A positive integer of the width of the bins for grouping. |

Value

A data frame

See Also

Other tabulate: [ypr_tabulate_biomass\(\)](#), [ypr_tabulate_parameters\(\)](#), [ypr_tabulate_sr\(\)](#),
[ypr_tabulate_yields\(\)](#), [ypr_tabulate_yield\(\)](#)

Examples

```
ypr_tabulate_fish(ypr_population())
```

`ypr_tabulate_parameters` *Tabulate Population Parameters*

Description

Tabulate Population Parameters

Usage

```
ypr_tabulate_parameters(population)
```

Arguments

- | | |
|-------------------------|---|
| <code>population</code> | An object of class ypr_population() . |
|-------------------------|---|

Value

A table of population parameters

See Also

[ypr_detabulate_parameters\(\)](#)

Other tabulate: [ypr_tabulate_biomass\(\)](#), [ypr_tabulate_fish\(\)](#), [ypr_tabulate_sr\(\)](#), [ypr_tabulate_yields\(\)](#), [ypr_tabulate_yield\(\)](#)

Examples

```
ypr_tabulate_parameters(ypr_population())
```

ypr_tabulate_sr *Tabulate Stock-Recruitment Parameters*

Description

Tabulate Stock-Recruitment Parameters

Usage

```
ypr_tabulate_sr(object, ...)

## S3 method for class 'ypr_population'
ypr_tabulate_sr(
  object,
  Ly = 0,
  harvest = TRUE,
  biomass = FALSE,
  all = FALSE,
  ...
)

## S3 method for class 'ypr_populations'
ypr_tabulate_sr(
  object,
  Ly = 0,
  harvest = TRUE,
  biomass = FALSE,
  all = FALSE,
  ...
)
```

Arguments

<code>object</code>	The populations or populations.
<code>...</code>	Unused parameters.
<code>Ly</code>	The minimum length (trophy) fish to consider when calculating the yield (cm).
<code>harvest</code>	A flag specifying whether to calculate the yield for harvested fish or captures.
<code>biomass</code>	A flag specifying whether to calculate the yield in terms of the biomass versus number of individuals.
<code>all</code>	A flag specifying whether to include all parameter values.

Value

A data.frame of stock-recruitment parameters.

Methods (by class)

- `ypr_population`: Tabulate Stock-Recruitment Parameters
- `ypr_populations`: Tabulate Stock-Recruitment Parameters

See Also

Other tabulate: [ypr_tabulate_biomass\(\)](#), [ypr_tabulate_fish\(\)](#), [ypr_tabulate_parameters\(\)](#), [ypr_tabulate_yields\(\)](#), [ypr_tabulate_yield\(\)](#)

Examples

```
ypr_tabulate_sr(ypr_population()) # Beverton-Holt
ypr_tabulate_sr(ypr_population(BH = 0L)) # Ricker
ypr_tabulate_sr(ypr_populations(Rk = c(2.5, 4.6)))
```

`ypr_tabulate_yield` *Tabulate Yield*

Description

Tabulate Yield

Usage

```
ypr_tabulate_yield(object, ...)

## S3 method for class 'ypr_population'
ypr_tabulate_yield(
  object,
  Ly = 0,
  harvest = TRUE,
  biomass = FALSE,
```

```

type = "both",
all = FALSE,
...
)

## S3 method for class 'ypr_populations'
ypr_tabulate_yield(
  object,
  Ly = 0,
  harvest = TRUE,
  biomass = FALSE,
  type = "both",
  all = FALSE,
  ...
)

```

Arguments

object	The populations or populations.
...	Unused parameters.
Ly	The minimum length (trophy) fish to consider when calculating the yield (cm).
harvest	A flag specifying whether to calculate the yield for harvested fish or captures.
biomass	A flag specifying whether to calculate the yield in terms of the biomass versus number of individuals.
type	A string indicating whether to include 'both' or just the 'actual' or 'optimal' yield.
all	A flag specifying whether to include all parameter values.

Value

A data frame.

Methods (by class)

- `ypr_population`: Tabulate Yield
- `ypr_populations`: Tabulate Yield

See Also

Other tabulate: [ypr_tabulate_biomass\(\)](#), [ypr_tabulate_fish\(\)](#), [ypr_tabulate_parameters\(\)](#), [ypr_tabulate_sr\(\)](#), [ypr_tabulate_yields\(\)](#)

Examples

```

ypr_tabulate_yield(ypr_population())
ypr_tabulate_yield(ypr_populations(Rk = c(3, 5)))

```

`ypr_tabulate_yields` *Tabulate Yields*

Description

Tabulate Yields

Usage

```
ypr_tabulate_yields(object, ...)

## S3 method for class 'ypr_population'
ypr_tabulate_yields(
  object,
  pi = seq(0, 1, length.out = 100),
  Ly = 0,
  harvest = TRUE,
  biomass = FALSE,
  all = FALSE,
  ...
)

## S3 method for class 'ypr_populations'
ypr_tabulate_yields(
  object,
  pi = seq(0, 1, length.out = 100),
  Ly = 0,
  harvest = TRUE,
  biomass = FALSE,
  all = FALSE,
  ...
)
```

Arguments

<code>object</code>	The populations or populations.
<code>...</code>	Unused parameters.
<code>pi</code>	A vector of probabilities of capture to calculate the yield for.
<code>Ly</code>	The minimum length (trophy) fish to consider when calculating the yield (cm).
<code>harvest</code>	A flag specifying whether to calculate the yield for harvested fish or captures.
<code>biomass</code>	A flag specifying whether to calculate the yield in terms of the biomass versus number of individuals.
<code>all</code>	A flag specifying whether to include all parameter values.

Value

A data frame.

Methods (by class)

- `ypr_population`: Tabulate Yields
- `ypr_populations`: Tabulate Yields

See Also

Other tabulate: `ypr_tabulate_biomass()`, `ypr_tabulate_fish()`, `ypr_tabulate_parameters()`,
`ypr_tabulate_sr()`, `ypr_tabulate_yield()`

Examples

```
ypr_tabulate_yields(ypr_population())
ypr_tabulate_yields(ypr_populations(Rk = c(3, 5)), pi = seq(0, 1, length.out = 10))
```

ypr_yield

Yield

Description

Calculates the yield for a population.

Usage

```
ypr_yield(population, Ly = 0, harvest = TRUE, biomass = FALSE)
```

Arguments

- | | |
|-------------------------|--|
| <code>population</code> | An object of class <code>ypr_population()</code> . |
| <code>Ly</code> | The minimum length (trophy) fish to consider when calculating the yield (cm). |
| <code>harvest</code> | A flag specifying whether to calculate the yield for harvested fish or captures. |
| <code>biomass</code> | A flag specifying whether to calculate the yield in terms of the biomass versus number of individuals. |

Details

By default, with `Rmax = 1` the number of individuals is the proportion of the recruits at the carrying capacity. If the yield is given in terms of the biomass (kg) then the scaling also depends on the value of `Wa` (g).

Value

The yield as number of fish or biomass.

See Also

[ypr_population\(\)](#) and [ypr_optimize\(\)](#)

Examples

```
ypr_yield(ypr_population())
```

ypr_yields

Yields

Description

Calculates the yield(s) for a population based on one or more capture rates.

Usage

```
ypr_yields(
  population,
  pi = seq(0, 1, length.out = 100),
  Ly = 0,
  harvest = TRUE,
  biomass = FALSE
)
```

Arguments

<code>population</code>	An object of class ypr_population() .
<code>pi</code>	A vector of probabilities of capture to calculate the yield for.
<code>Ly</code>	The minimum length (trophy) fish to consider when calculating the yield (cm).
<code>harvest</code>	A flag specifying whether to calculate the yield for harvested fish or captures.
<code>biomass</code>	A flag specifying whether to calculate the yield in terms of the biomass versus number of individuals.

Value

A numeric vector of the yields.

See Also

[ypr_yield\(\)](#)

Examples

```
pi <- seq(0, 1, length.out = 30)
plot(pi, ypr_yields(ypr_population(), pi), type = "l")
```

Index

* **datasets**

- adams_bt_03, 3
- chilliwack_bt_05, 5
- kootenay_bt_13, 5
- kootenay_rb, 6
- kootenay_rb_13, 7
- quesnel_bt, 8
- quesnel_lt, 9
- quesnel_rb, 9

* **tabulate**

- ypr_tabulate_biomass, 27
- ypr_tabulate_fish, 28
- ypr_tabulate_parameters, 28
- ypr_tabulate_sr, 29
- ypr_tabulate_yield, 30
- ypr_tabulate_yields, 32

- adams_bt_03, 3
- as_ypr_population, 3
- as_ypr_populations, 4

- chilliwack_bt_05, 5

- ggplot2::geom_histogram(), 15, 16
- graphics::plot, 8

- kootenay_bt_13, 5
- kootenay_rb, 6
- kootenay_rb(), 7
- kootenay_rb_13, 7

- plot.ypr_population, 7

- quesnel_bt, 8
- quesnel_lt, 9
- quesnel_rb, 9

- update.ypr_population, 10
- update.ypr_populations, 11

- ypr_age_at_length, 12

- ypr_databulate_parameters, 12
- ypr_databulate_parameters(), 29
- ypr_exploitation, 13
- ypr_length_at_age, 14
- ypr_optimise (ypr_optimize), 14
- ypr_optimize, 14
- ypr_optimize(), 23, 34
- ypr_plot_biomass, 15
- ypr_plot_fish, 16
- ypr_plot_schedule, 17
- ypr_plot_sr, 17
- ypr_plot_yield, 18
- ypr_plot_yield.ypr_population, 19
- ypr_plot_yield.ypr_populations, 20
- ypr_population, 21
- ypr_population(), 3, 6–19, 23–28, 33, 34
- ypr_population_names, 24
- ypr_population_update
 - (update.ypr_population), 10
- ypr_population_update(), 23
- ypr_populations, 23
- ypr_populations(), 5, 11, 21, 24
- ypr_populations_expand, 24
- ypr_populations_update
 - (update.ypr_populations), 11
- ypr_report, 25
- ypr_schedule, 26
- ypr_sr, 26
- ypr_sr(), 18
- ypr_tabulate_biomass, 27, 28–31, 33
- ypr_tabulate_fish, 27, 28, 29–31, 33
- ypr_tabulate_parameters, 27, 28, 28, 30, 31, 33
- ypr_tabulate_parameters(), 13
- ypr_tabulate_schedule (ypr_schedule), 26
- ypr_tabulate_schedule(), 8, 17, 23
- ypr_tabulate_sr, 27–29, 29, 31, 33
- ypr_tabulate_yield, 27–30, 30, 33
- ypr_tabulate_yields, 27–31, 32

ypr_yield, [33](#)
ypr_yield(), [15](#), [23](#), [34](#)
ypr_yields, [34](#)
ypr_yields(), [18](#), [19](#), [21](#)